



# Power terminal blocks

- Wire size up to 1000 MCM
- IP20 Protection cover
- Holding foot on DIN 3 rail with two positions for easy mounting
- Lugs mounting according NFC 20130 and DIN 46234
- Many marking possibilities
- Rail or base mounting







## Stud - Stud

Block	Rated wire size	Spacing	Rated current	Part/number	Protective cover	Jumper bar
 <b>D 35/27.FF</b>	<b>1 AWG</b>	27 mm	125 A	With cover : Grey <b>0190 033.17</b> Without cover : Grey <b>0190 001.20</b>	Grey <b>0190 016.16</b>	2 poles <b>0205 772.13</b> 3 poles <b>0205 773.14</b>
 <b>D 70/32.FF</b>	<b>3/0 AWG</b>	32 mm	170 A	With cover : Grey <b>0190 034.10</b> Without cover : Grey <b>0190 002.21</b>	Grey <b>0190 017.17</b>	2 poles <b>0205 774.15</b> 3 poles <b>0205 775.16</b>
 <b>D 120/42.FF</b>	<b>300 MCM</b>	42 mm	269 A	With cover : Grey <b>0190 035.11</b> Without cover : Grey <b>0190 003.22</b>	Grey <b>0190 018.20</b>	2 poles <b>0205 776.17</b> 3 poles <b>0205 777.10</b>
 <b>D 185/55.FF</b>	<b>500 MCM</b>	55 mm	353 A	With cover : Grey <b>0190 036.12</b> Without cover : Grey <b>0190 004.23</b>	Grey <b>0190 019.21</b>	2 poles <b>0205 778.21</b> 3 poles <b>0205 779.22</b>
 <b>D 300/55.FF</b>	<b>1000 MCM</b>	55 mm	460 A	With cover : Grey <b>0190 037.13</b> Without cover : Grey <b>0190 005.24</b>	Grey <b>0190 019.21</b>	2 poles <b>0205 778.21</b> 3 poles <b>0205 779.22</b>



## Stud - Screw clamp

Block	Rated wire size	Spacing	Rated current	Part/number	Cover	Jumper bar
 <b>D 35/27.AF</b>	<b>12-1 AWG</b>	27 mm	130 A	With cover Grey <b>0190 006.25</b>	Grey <b>0190 016.16</b>	2 poles <b>0205 772.13</b> 3 poles <b>0205 773.14</b>
 <b>D 70/32.AF</b>	<b>10-3/0 AWG</b>	32 mm	165 A	With cover Grey <b>0190 007.26</b>	Grey <b>0190 017.17</b>	2 poles <b>0205 774.15</b> 3 poles <b>0205 775.16</b>
 <b>D 120/42.AF</b>	<b>10 AWG - 300 MCM</b>	42 mm	240 A	With cover Grey <b>0190 008.07</b>	Grey <b>0190 018.20</b>	2 poles <b>0205 776.17</b> 3 poles <b>0205 777.10</b>
 <b>D 185/55.AF</b>	<b>4 AWG - 500 MCM</b>	55 mm	320 A	With cover Grey <b>0190 009.00</b>	Grey <b>0190 019.21</b>	2 poles <b>0205 778.21</b> 3 poles <b>0205 779.22</b>



---

**ABB Inc.**  
1206 Hatton Road  
Wichita Falls, TX 76302  
Telephone 888-385-1221; 940-397-7000  
Fax 940-397-7085  
<http://www.abb-control.com>

Publication  
No. 1SXU 160 005 B0201 (LV005)  
Printed in USA, October, 2004