


- NOTES:
1. ENCLOSURE TO BE LABELED UL TYPE 1.
 2. ENCLOSURE IS 16GA. STEEL.
 3. ENCLOSURE PROVIDED WITH 14GA. WHITE PAINTED PRE-PUNCHED SUB PANEL. REFER TO DRAWING D 5492 1001-001.
 4. SCE-CONCEALED HINGE USED ON DOOR.
 5. GROUND STUDS ON BODY AND DOOR.
 6. SUB PANEL IS MOUNTED ON 1/4-20 X 9/16 HIGH B50.S.
 7. SCE-MINQB 1/4 TURN LATCHES TWO PLACES ON DOOR.
 8. .890 PUSH BUTTON HOLES (WITH HOLE PLUGS PROVIDED BY SCE) IN RIGHT FLANGE.

F	ADDED REFER TO DRAWING D 5492 1001-001 TO NOTE 3.	1/16/06	WRH	DO NOT SCALE DRAWING		THIS DRAWING IS THE PROPERTY OF ABB Inc. AND CONTAINS PROPRIETARY AND CONFIDENTIAL INFORMATION WHICH MUST NOT BE DUPLICATED, COPIED OR DISSEMINATED WITHOUT THE AUTHORIZATION BY ABB Inc.		DATE	3/24/05	REV.	F	TITLE	UL TYPE 1 ENCLOSURE	
E	TOP VIEW & BOTTOM VIEW L.H. & R.H. KNOCKOUTS WERE 1.1-1/2, 2, & 3. 3.250 SPACING BETWEEN KNOCKOUTS.	8/10/05	TSP	SCALE	3/64"			DIMENSIONS ARE IN INCHES	DRAWN	DW	SIZE	F	DRAWING NUMBER	24 X 48 X 12
C	WAS 3.125.	6/17/05	DW	Material:	24X48X12 TYPE 1			Finish: ANSI 61 LIGHT GREY	CHK'D					
B	ADDED KEY SLOT FOR 3/8 BOLT TO CENTER HANGING EAR.	4/4/05	TSP	STANDARD TOLERANCES	2 PL DEC. ±.030			3 PL DEC. ±.030	APPR'D				A	D 5491 0001-010
REV. LET.	REVISIONS	DATE	REV OR APPD BY	ANGLES ±1°			SHEET	1	OF	1				