


INPUT VOLTAGE	OUTPUT VOLTAGE
H4-H3	H4-H2
240	240
480	480
208	230
220	220
440	440
	23
	110

NOTE: IF BOTH OUTPUTS ARE USED 200VA MAXIMUM VA RATING SHOULD BE SHOWN ON THE TRANSFORMER WITH 25 PERCENTAGE OF

PRIMARY IDENTIFICATION LABEL  
SECONDARY IDENTIFICATION LABEL  
CONNECTION TABLE LABEL

Transformer Specifications	
PRIMARY VOLTAGE(S)	208/230/460 (TRIPLE)
SECONDARY VOLTAGE(S)	24/115
RATED V/A	100
RATED FREQUENCY	50/60
INSULATION CLASS	105
AGENCY APPROVALS	UL,CUL
ESTIMATED WEIGHT	6.8 LBS



NOTE:  
1. TORQUE CONNECTIONS TO 16 LB-IN  
2. FUSE CLIPS TO ACCOMMODATE 13/32-1 1/2"

**MICRON CONTROL TRANSFORMER**

**MICRON INDUSTRIES CORPORATION**  
777 CHURCH ROAD - ELMHURST, IL 60126  
Tel. (800)664-4660, (630)516-1222 Fax (630)516-1820  
www.microntransformers.com

DATE	1/15/08	DRAWN	J.G.V.	CHECKED	APPROVED
RELEASE DATE		CUST. P/N			

OUTLINE DRAWING

SIZE: A SCALE: NONE

B100-0418-8