

Product News LOW VOLTAGE PRODUCTS

Ref. to Brochure 1SFC151001B0201 September 2003

Ident. No. **1SFC151010K0201**

Date November, 18 2003

Pilot Devices, Compact Range Compact Pilot Light with integrated LED

The Pilot Devices Compact Range has now been enlarged with compact pilot lights with integrated LED

Rated voltage V	Rated current (mA)	Type of current	Color	Lumi- nance (mcd)	Wave- length (nm)	Type	Order Code	EAN 7320500...	Weight kg
12 ¹⁾	30	DC	Red	60	625	CL-501R	1SFA619402R5011	250235	0.023
12 ¹⁾	15	DC	Green	126	520	CL-501G	1SFA619402R5012	250242	0.023
12 ¹⁾	30	DC	Yellow	60	590	CL-501Y	1SFA619402R5013	250259	0.023
12 ¹⁾	30	DC	Blue	22	470	CL-501L	1SFA619402R5014	250266	0.023
12 ¹⁾	30	DC	White	88	x=3 y=3	CL-501W	1SFA619402R5015	250273	0.023
24	15	AC/DC	Red	60	625	CL-502R	1SFA619402R5021	250280	0.023
24	15	AC/DC	Green	126	520	CL-502G	1SFA619402R5022	250297	0.023
24	15	AC/DC	Yellow	60	590	CL-502Y	1SFA619402R5023	250303	0.023
24	15	AC/DC	Blue	22	470	CL-502L	1SFA619402R5024	250310	0.023
24	15	AC/DC	White	88	x=3 y=3	CL-502W	1SFA619402R5025	250327	0.023
48	15	AC/DC	Red	60	625	CL-504R	1SFA619402R5041	250334	0.023
48	15	AC/DC	Green	126	520	CL-504G	1SFA619402R5042	250341	0.023
48	15	AC/DC	Yellow	60	590	CL-504Y	1SFA619402R5043	250358	0.023
48	15	AC/DC	Blue	22	470	CL-504L	1SFA619402R5044	250365	0.023
48	15	AC/DC	White	88	x=3 y=3	CL-504W	1SFA619402R5045	250372	0.023
60	15	AC/DC	Red	60	625	CL-505R	1SFA619402R5051	259429	0.023
60	15	AC/DC	Green	126	520	CL-505G	1SFA619402R5052	259436	0.023
60	15	AC/DC	Yellow	60	590	CL-505Y	1SFA619402R5053	259443	0.023
60	15	AC/DC	Blue	22	470	CL-505L	1SFA619402R5054	259450	0.023
60	15	AC/DC	White	88	x=3 y=3	CL-505W	1SFA619402R5055	259467	0.023
110-130	15	AC	Red	60	625	CL-513R	1SFA619402R5131	259320	0.023
110-130	15	AC	Green	126	520	CL-513G	1SFA619402R5132	259337	0.023
110-130	15	AC	Yellow	60	590	CL-513Y	1SFA619402R5133	259344	0.023
110-130	15	AC	Blue	22	470	CL-513L	1SFA619402R5134	259351	0.023
110-130	15	AC	White	88	x=3 y=3	CL-513W	1SFA619402R5135	259368	0.023
110-130	15	DC	Red	60	625	CL-515R	1SFA619402R5151	259375	0.023
110-130	15	DC	Green	126	520	CL-515G	1SFA619402R5152	259382	0.023
110-130	15	DC	Yellow	60	590	CL-515Y	1SFA619402R5153	259399	0.023
110-130	15	DC	Blue	22	470	CL-515L	1SFA619402R5154	259405	0.023
110-130	15	DC	White	88	x=3 y=3	CL-515W	1SFA619402R5155	259412	0.023
230	15	AC	Red	60	625	CL-523R	1SFA619402R5231	250488	0.023
230	15	AC	Green	126	520	CL-523G	1SFA619402R5232	250495	0.023
230	15	AC	Yellow	60	590	CL-523Y	1SFA619402R5233	250501	0.023
230	15	AC	Blue	22	470	CL-523L	1SFA619402R5234	253861	0.023
230	15	AC	White	88	x=3 y=3	CL-523W	1SFA619402R5235	250525	0.023

¹⁾ Care should be taken for 12 V version where + and - must be correctly installed (this is marked on the product, X1 (+) and X2 (-)).

Ident.nr **1SFC151010K0201**
ABB Automation Technology Products AB/Control, SE-721 61 Västerås, Sweden, Phone +46 21 320700, Fax +46 21 126001

