

# Fuse holder terminal blocks

5x20 mm .197x.787 in. and 5x25 mm .197x.984 in.  
Screw clamp, DIN 1 - DIN3

## M 4/8.SF- 4 mm<sup>2</sup> blocks - 8 mm .315" spacing

### Characteristics

		IEC NFC	DIN	UL	CSA
Wire size mm <sup>2</sup> / AWG	Solid	0.5 - 6		22-12 AWG	22-12 AWG
	Stranded	0.5 - 4			
Voltage	V	630 ①②		600 ①	250
Current	A	6.3		10	10
Rated wire size	mm <sup>2</sup> / AWG	4 mm <sup>2</sup>		12 AWG	12 AWG
Wire stripping length	mm / inches	9.5 mm / .37"			
Recommended torque	Nm / lb.in	0.5-0.8 Nm / 4.4-7.1 lb.in			

### Selection

Description	Type	Catalog Number	Packaging
Standard block grey	M 4/8.SF	1SNA 115 657 R2500	50
Block with test socket Ø2 mm grey	M 4/8.SF	1SNA 115 662 R2200	50
Standard block orange	M 4/8.SF2	1SNA 105 135 R1100	50
Standard block beige V0	M 4/8.SF.V0	1SNA 195 657 R2600	50

## M 4/8.SFL - 4 mm<sup>2</sup> blocks - 8 mm .315" spacing

### Characteristics

		IEC NFC	DIN	UL	CSA
Wire size mm <sup>2</sup> / AWG	Solid	0.5 - 6		22-12 AWG	22-12 AWG
	Stranded	0.5 - 4			
Voltage	V	400		600	250
Current	A	6.3		10	10
Rated wire size	mm <sup>2</sup> / AWG	4 mm <sup>2</sup>		12 AWG	12 AWG
Wire stripping length	mm / inches	9.5 mm / .374"			
Recommended torque	Nm / lb.in	0.5-0.8 Nm / 4.4-7.7 lb.in			

### Selection

Description	Type	Catalog Number	Packaging
Block with fusion indicator neon grey	M 4/8.SFL	1SNA 115 661 R2100	50
Block with fusion indicator 24V grey	M 4/8.SFD	1SNA 115 663 R2300	50

## M 4/8.SN - 4 mm<sup>2</sup> blocks - 8 mm .315" spacing

### Characteristics

		IEC NFC	DIN	UL	CSA
Wire size mm <sup>2</sup> / AWG	Solid	0.5 - 6		22-12 AWG	24-12 AWG
	Stranded	0.5 - 4			
Voltage	V	630 ①		600	250
Current	A	6.3		10	10
Rated wire size	mm <sup>2</sup> / AWG	4 mm <sup>2</sup>		12 AWG	12 AWG
Wire stripping length	mm / inches	9.5 mm / .37"			
Recommended torque	Nm / lb.in	0.5-0.8 Nm / 4.4-7.1 lb.in			

### Selection

Description	Type	Catalog Number	Packaging
Standard block grey body/blue grip	M 4/8.SN	1SNA 115 659 R0700	50
Standard block beige body/blue V0 grip	M 4/8.SN.V0	1SNA 195 659 R0000	50

### Accessories

Description	Type	Catalog Number	Packaging
End stop	BAM2 9.9 mm	1SNA 206 351 R1600	50
End section	grey	FEM8S 1.5 mm	1SNA 116 951 R1500
	orange	FEM8S 1.5 mm	1SNA 103 923 R1500

① Insulation voltage of terminal block - operating voltage : according to fuse.  
② 400 V for block M 4/6.SFT

