



Feed through and ground terminal blocks

Screw clamp, DIN 1-3




MA 2,5/5




BAM2




FEM6




SCF6



BJMI5




CBM...



MA 2,5/5.P



FEM6



SCF6

MA 2,5/5 - 2.5 mm² blocks - 5 mm .200" spacing

Characteristics

Wire size mm ² / AWG	Solid Stranded	IEC	UL	CSA
		NFC DIN		
		0.2 - 4	22-12 AWG	22-12 AWG
Voltage		800	600	600
Current	A	24	30	25
Short circuit current (MA 2,5/5.PI)	A / s	300A/1s		
Rated wire size	mm ² / AWG	2.5 mm ²	12 AWG	12 AWG
Wire stripping length	mm / inches	10 mm / .39"		
Recommended torque	Nm / lb.in	0.4-0.6 Nm / 3.5-5.3 lb.in		

Selection

Description	Type	Catalog Number	Packaging
Standard block grey	MA 2,5/5	1SNA 115 486 R0300	50
Standard block white	MA 2,5/5	1SNA 105 052 R2100	50
Standard block blue	MA 2,5/5.N	1SNA 125 486 R0500	50
Standard block yellow	MA 2,5/5	1SNA 105 486 R1200	50
Standard block orange	MA 2,5/5	1SNA 105 075 R2000	50
Standard block black	MA 2,5/5	1SNA 105 077 R2300	50
Standard block red	MA 2,5/5	1SNA 400 184 R2700	50
Standard block beige V0	MA 2,5/5.V0	1SNA 195 486 R0400	50
Ground block yellow body/ green marking (without rail contact)	MA 2,5/5.PI	1SNA 165 677 R0300	50

Accessories

End stop	BAM2	9.9 mm	1SNA 103 002 R2600	50
End section	grey ①	FEM6 2.8 mm	1SNA 118 368 R1600	20
	blue ①	FEM6 2.8 mm	1SNA 128 368 R1000	20
	orange ①	FEM6 2.8 mm	1SNA 103 126 R1600	20
	yellow ①	FEM6 2.8 mm	1SNA 103 062 R2100	20
	green ①	FEM6 2.8 mm	1SNA 103 125 R1500	20
Separator end section	grey	SCF6 3 mm	1SNA 118 707 R0300	20
Assembled jumper bar (with IP20 protection)	2 poles	BJMI5 24 A	1SNA 176 278 R1600	10
	3 poles	BJMI5 24 A	1SNA 176 279 R1700	10
	4 poles	BJMI5 24 A	1SNA 176 280 R0500	10
	5 poles	BJMI5 24 A	1SNA 176 281 R2200	10
	10 poles	BJMI5 24 A	1SNA 176 282 R2300	10
Shield connector	CBM5	0.5 mm	1SNA 178 745 R1400	20
	CBM8	0.8 mm	1SNA 178 746 R1500	20

MA 2,5/5.P - 2.5 mm² ground block with rail contact - 5 mm .200" spacing

Characteristics

Wire size mm ² / AWG	Solid Stranded	IEC	UL	CSA
		NFC DIN		
		0.2 - 4	22-12 AWG	22-12 AWG
		0.22 - 2.5		
Short circuit current	A / s	300A/1s		
Rated wire size	mm ² / AWG	2.5 mm ²	12 AWG	12 AWG
Wire stripping length	mm / inches	10 mm / .39"		
Recommended torque	Nm / lb.in	0.4-0.6 Nm / 3.5-5.3 lb.in		

Selection

Description	Type	Catalog Number	Packaging
Ground block V2 green/yellow	MA 2,5/5.P	1SNA 165 488 R2700	50
Mounting on DIN 3 rail without screw : Ground block V2 green/yellow	D 2,5/5.P	1SNA 165 909 R0500	50

Accessories

End section	yellow	FEM6 2.8 mm	1SNA 103 062 R2100	20
	yellow V0	FEM6 V0 2.8 mm	1SNA 199 305 R0200	20
Separator end section	grey	SCF6 3 mm	1SNA 118 707 R0300	20

① Other colors available. Please consult factory.