

Feed through and ground terminal blocks

Insulation displacement

ADO - ADO, DIN 3

D 1/5.ADO - 1 mm² blocks - 5 mm .198" spacing

Characteristics

Wire size mm ² / AWG	Screw	IEC NFC DIN			UL	CSA
		Solid	Stranded	ADO		
	ADO	Solid	0.2 - 1	24-18 AWG	24-18 AWG	
		Stranded	0.22 - 1			
Voltage		V	1000	600	600	
Current		A	13.5	7	7	
Short circuit current (D 1/5.PI.ADO)		A / s	120 A/1s			
Rated wire size		mm ² / AWG	1 mm ²	18 AWG	18 AWG	

2 wires of the same gauge and nature per ADO connection

Selection

Description	Type	Catalog Number	Packaging
Standard block grey	D 1/5.ADO	1SNA 199 563 R2400	50
Standard block orange	D 1/5.ADO	1SNA 199 564 R2500	50
Standard block blue	D 1/5.N.ADO	1SNA 199 565 R2600	50
Standard block black	D 1/5.ADO	1SNA 199 566 R2700	50
Standard block red	D 1/5.ADO	1SNA 199 567 R2000	50
Standard block yellow	D 1/5.ADO	1SNA 199 569 R0200	50
Standard block ivory	D 1/5.ADO	1SNA 199 568 R0100	50
Standard block green	D 1/5.ADO	1SNA 199 570 R0700	50
Ground block yellow body/ green marking (without rail contact)	D 1/5.PI.ADO	1SNA 399 184 R2100	50

Accessories

End stop		BADL	9 mm	1SNA 399 903 R0200	50
		BAM2	9.9 mm	1SNA 399 967 R0100	50
End section	grey	FEMAD3	3 mm	1SNA 199 341 R0500	20
	yellow	FEMAD3	3 mm	1SNA 199 343 R0700	20
Assembled jumper bar (with IP20 protection)	2 poles	BJMI5	24 A	1SNA 176 278 R1600	10
	3 poles	BJMI5	24 A	1SNA 176 279 R1700	10
	4 poles	BJMI5	24 A	1SNA 176 280 R0500	10
	5 poles	BJMI5	24 A	1SNA 176 281 R2200	10
	10 poles	BJMI5	24 A	1SNA 176 282 R2300	10
Shield connector		CBM5	0.5 mm	1SNA 178 745 R1400	50
		CBM8	0.8 mm	1SNA 178 746 R1500	50

D 1/5.PADO - 1 mm² ground block with rail contact - 5 mm .198" spacing

Characteristics

Wire size mm ² / AWG	Screw	IEC NFC DIN			UL	CSA
		Solid	Stranded	ADO		
	ADO	Solid	0.2 - 1	24-18AWG	24-18AWG	
		Stranded	0.22 - 1			
Short circuit current		A / s	120 A/1s			
Rated wire size		mm ² / AWG				


2 wires of the same gauge and nature per ADO connection

Selection



Description	Type	Catalog Number	Packaging
Ground block green body/yellow marking	D 1/5.PADO	1SNA 399 031 R2200	50

Accessories


End section	yellow	FEMAD3	3 mm	1SNA 199 343 R0700	20
	grey	FEMAD3	3 mm	1SNA 199 341 R0500	20



D 1/5.ADO



D 1/5.PADO



FEMAD3