

16A – 100A, Base & DIN rail mounted Handles & shafts

Disconnect
switches
Non-fusible



Pistol handles – for use with shafts $\square .20 \times .20$ " ($\square 5 \times 5$ mm)

UL/NEMA type	IEC type	Color	Marking	Length inches/mm	Defeatable	Padlockable	Weight (lbs.)	Catalog number	List price
1,3R,12	IP65	Black	O/I & Off/On	1.8/45	Yes	Yes	0.28	OHB45J5	\$ 70
1,3R,12	IP65	Red/Yel	O/I & Off/On	1.8/45	Yes	Yes	0.28	OHY45J5	70
1,3R,12	IP65	Black	O/I & Off/On	2.6/65	Yes	Yes	0.29	OHB65J5	80
1,3R,12	IP65	Red/Yel	O/I & Off/On	2.6/65	Yes	Yes	0.29	OHY65J5	80
1,3R,12,4,4X	IP66	Black	O/I & Off/On	2.6/65	Yes	Yes	0.29	OHB65L5	120
1,3R,12,4,4X	IP66	Red/Yel	O/I & Off/On	2.6/65	Yes	Yes	0.29	OHY65L5	120
1,3R,12,4,4X	IP66	Stainless Steel	O/I & Off/On	1.8/45	Yes	Yes	1.40	OHM45L5	700
				2.6/65			1.60	OHM65L5	700

Shafts – for use with pistol handles $\square .20 \times .20$ " ($\square 5 \times 5$ mm)

Shaft length (inches/mm)	Mounting depth ^① (inches)			Weight (lbs.)	Catalog number	List price
	OT16E3 OT25E3 OT32E3	OT45E3 OT63E3	OT30E3 OT60E3 OT100E3			
5.9/150	6.2 – 6.7	6.9 – 7.4	6.4 – 7.4	0.07	OXPSX150	\$ 14
6.7/170	7.0 – 7.5	7.7 – 8.1	7.2 – 8.1	0.08	OXPSX170	16
10.4/265	10.7 – 11.3	11.4 – 11.9	10.9 – 11.9	0.12	OXPSX265	18
15.8/400	16.0 – 16.6	16.8 – 17.2	16.2 – 17.2	0.18	OXPSX400	30
19.7/500	20.0 – 20.5	20.7 – 21.1	20.1 – 21.1	0.23	OXPSX500	42

Twisted shafts – Rotates handle 45° $\square .20 \times .20$ " ($\square 5 \times 5$ mm)

Shaft length (inches/mm)	Mounting depth ^① (inches)			Weight (lbs.)	Catalog number	List price
	OT16E3 OT25E3 OT32E3	OT45E3 OT63E3	OT30E3 OT60E3 OT100E3			
5.9/150	6.2 – 6.7	6.9 – 7.4	6.4 – 7.4	0.07	OXPSX150-45	\$ 14
6.7/170	7.0 – 7.5	7.7 – 8.1	7.2 – 8.1	0.08	OXPSX170-45	16
10.4/265	10.7 – 11.3	11.4 – 11.9	10.9 – 11.9	0.12	OXPSX265-45	18
15.8/400	16.0 – 16.6	16.8 – 17.2	16.2 – 17.2	0.18	OXPSX400-45	30
19.7/500	20.0 – 20.5	20.7 – 21.1	20.1 – 21.1	0.23	OXPSX500-45	42

Replacement knob – mounts directly to switch; no shaft necessary

UL/NEMA Type	Color	For use on:	Length (inches)	Padlockable	Catalog number	List price
1	Red	OT16, OT25, OT32	1.0	–	CXBY68135	\$ 8
1	Red	OT30, OT45 – OT100	1.4	–	CXBY68306	12
1	Red	OT30, OT45 – OT100	1.6	Yes ^②	CXBY68419/1	14
Metal collar		OT16 – OT100	–	–	OTZS1	13
Set screw		OT16 – OT100	–	–	FLSWM5XAX	2 ^③

Modular adapter cover – for OT16, OT25, OT32

Item	For use	Length (inches)	Padlockable (inches)	Catalog number	List price
Adapter cover	OT16, OT25 OT32	–	Yes	OHY7	\$ 28

A padlock can be used with the adapter cover.

^① Mounting depth is the distance from the outside of door to the disconnect switch mounting plate. Shaft can be cut to desired length.

^② .1875" (3/16") diameter shackle required.

^③ Set screw FLSWM5XAX needed with replacement knobs CXBY__.