

30A, Base & DIN rail mounted UL fuse Class J,CC

Disconnect
switches
Fusible

For a complete assembly,
please select one of each:

- 1 switch
- 1 handle
- 1 shaft



OS30AJ12



OXS5X180



OHB2AJ1




OS30A_12



OHB2_



OHY2_



OXS5X_

30 Amp switches, 600V

UL general purpose amp rating	UL Fuse type 600V	Maximum horsepower rating			Terminal lugs		Catalog number	List price
		Three phase			Wire size	Wire type		
		240V	480V	600V				
3 pole							3 pole	
30	J	7.5	15	20	#18 - 8	Cu	OS30AJ12	\$ 280
30 [Ⓞ]	CC	7.5	15	20	#18 - 8	Cu	OS30ACC12	
4 pole							4 Pole	
30	J	7.5	15	20	#18 - 8	Cu	OS30AJ22F	350
30 [Ⓞ]	CC	7.5	15	20	#18 - 8	Cu	OS30ACC22F	


Selector handles — for use with shafts $\square .20 \times .20"$ ($\square 5 \times 5 \text{ mm}$)

UL/NEMA type	IEC type	Color	Defeat- able	Padlock- able	Weight (lbs.)	Catalog number	List price
-----------------	-------------	-------	-----------------	------------------	------------------	-------------------	---------------

All marked both O/I & Off/On

1,3R,12	IP65	Black	—	Yes	0.16	OHB2AJ1	\$ 28
1,3R,12	IP65	Red/Yel	—	Yes	0.16	OHY2AJ1	28
1,3R,12	IP65	Blk	Yes	Yes	0.16	OHB2AJ	30
1,3R,12	IP65	Red/Yel	Yes	Yes	0.16	OHY2AJ	30

Shafts — for use with OH_2_ selector handles $\square .20 \times .20"$ ($\square 5 \times 5 \text{ mm}$)

Shaft length (inches/mm)		Mounting depth [Ⓞ] (in inches)	Weight (lbs.)	Catalog number	List price
3.3/85		5.5 - 5.7	0.04	OXS5X85	\$ 4
4.1/105		5.5 - 6.5	0.04	OXS5X105	4
4.7/120		5.5 - 7.1	0.05	OXS5X120	4
5.1/130		5.5 - 7.5	0.05	OXS5X130	6
7.1/180		6.3 - 9.4	0.08	OXS5X180	6
9.8/250		9.1 - 12.2	0.10	OXS5X250	12
13.0/330		12.2 - 15.4	0.14	OXS5X330	20

[Ⓞ] Rejection style fuses only.