

# Wye-delta, closed transition A26 - A750 Three phase

Reduced voltage  
starters

3

UL Type 3R (Outdoor metal)		Type 12 (Metal dusttight)		UL Type 4 (Watertight)		UL Type 4X (Stainless steel)	
Catalog number	List price	Catalog number	List price	Catalog number	List price	Catalog number	List price

### UL rated

A26SY3-84Δ‡	<b>\$ 5621</b>	A26SY2-84Δ‡	<b>\$ 5621</b>	A26SY4-84Δ‡	<b>\$ 5801</b>	A26SYX-84Δ‡	<b>\$ 6450</b>
A30SY3-84Δ‡	<b>5921</b>	A30SY2-84Δ‡	<b>5921</b>	A30SY4-84Δ‡	<b>6101</b>	A30SYX-84Δ‡	<b>6788</b>
A40SY3-84Δ‡	<b>6467</b>	A40SY2-84Δ‡	<b>6467</b>	A40SY4-84Δ‡	<b>6557</b>	A40SYX-84Δ‡	<b>7275</b>
A50SY3-84Δ‡	<b>6665</b>	A50SY2-84Δ‡	<b>6665</b>	A50SY4-84Δ‡	<b>6755</b>	A50SYX-84Δ‡	<b>7650</b>
A63SY3-84Δ‡	<b>8942</b>	A63SY2-84Δ‡	<b>8942</b>	A63SY4-84Δ‡	<b>9347</b>	A63SYX-84Δ‡	<b>10,163</b>
A75SY3-84Δ‡	<b>9689</b>	A75SY2-84Δ‡	<b>9689</b>	A75SY4-84Δ‡	<b>10,094</b>	A75SYX-84Δ‡	<b>11,138</b>
A95SY3-84Δ‡	<b>14,900</b>	A95SY2-84Δ‡	<b>14,900</b>	A95SY4-84Δ‡	<b>15,900</b>	A95SYX-84Δ‡	<b>17,000</b>
A110SY3-84Δ‡	<b>15,907</b>	A110SY2-84Δ‡	<b>15,907</b>	A110SY4-84Δ‡	<b>16,870</b>	A110SYX-84Δ‡	<b>18,350</b>
A145SY3-84Δ‡	<b>17,123</b>	A145SY2-84Δ‡	<b>17,023</b>	A145SY4-84Δ‡	<b>18,086</b>	A145SYX-84Δ‡	<b>19,950</b>
A185SY3-84Δ‡	<b>22,973</b>	A185SY2-84Δ‡	<b>22,973</b>	A185SY4-84Δ‡	<b>28,436</b>	A185SYX-84Δ‡	<b>30,225</b>
A210SY3-84Δ‡	<b>27,482</b>	A210SY2-84Δ‡	<b>27,482</b>	A210SY4-84Δ‡	<b>30,182</b>	A210SYX-84Δ‡	<b>32,400</b>
A260SY3-84Δ‡	<b>28,841</b>	A260SY2-84Δ‡	<b>28,841</b>	A260SY4-84Δ‡	<b>31,541</b>	A260SYX-84Δ‡	<b>33,450</b>
A300SY3-84Δ‡	<b>34,991</b>	A300SY2-84Δ‡	<b>34,991</b>	A300SY4-84Δ‡	<b>37,691</b>	A300SYX-84Δ‡	<b>40,688</b>
A400SY3-70Δ‡	<b>41,250</b>	A400SY2-70Δ‡	<b>41,250</b>	A400SY4-70Δ‡	<b>45,330</b>	A400SYX-70Δ‡	<b>48,675</b>
A460SY3-70Δ‡	<b>57,101</b>	A460SY2-70Δ‡	<b>57,101</b>	A460SY4-70Δ‡	<b>60,476</b>	A460SYX-70Δ‡	<b>66,900</b>
A580SY3-70Δ‡	<b>72,749</b>	A580SY2-70Δ‡	<b>72,749</b>	A580SY4-70Δ‡	<b>75,633</b>	A580SYX-70Δ‡	<b>83,625</b>
A750SY3-70Δ‡	<b>78,071</b>	A750SY2-70Δ‡	<b>78,071</b>	A750SY4-70Δ‡	<b>81,446</b>	A750SYX-70Δ‡	<b>88,725</b>

### NEMA rated

A26NSY3-84Δ‡	<b>\$ 5621</b>	A26NSY2-84Δ‡	<b>\$ 5621</b>	A26NSY4-84Δ‡	<b>\$ 5801</b>	A26NSYX-84Δ‡	<b>\$ 6450</b>
A50NSY3-84Δ‡	<b>6665</b>	A50NSY2-84Δ‡	<b>6665</b>	A50NSY4-84Δ‡	<b>6755</b>	A50NSYX-84Δ‡	<b>7650</b>
A75NSY3-84Δ‡	<b>9689</b>	A75NSY2-84Δ‡	<b>9689</b>	A75NSY4-84Δ‡	<b>10,094</b>	A75NSYX-84Δ‡	<b>11,138</b>
A145NSY3-84Δ‡	<b>17,123</b>	A145NSY2-84Δ‡	<b>17,023</b>	A145NSY4-84Δ‡	<b>18,086</b>	A145NSYX-84Δ‡	<b>19,950</b>
A260NSY3-84Δ‡	<b>28,841</b>	A260NSY2-84Δ‡	<b>28,841</b>	A260NSY4-84Δ‡	<b>31,541</b>	A260NSYX-84Δ‡	<b>33,450</b>
A460NSY3-70Δ‡	<b>57,101</b>	A460NSY2-70Δ‡	<b>57,101</b>	A460NSY4-70Δ‡	<b>60,476</b>	A460NSYX-70Δ‡	<b>66,900</b>
A750NSY3-70Δ‡	<b>78,071</b>	A750NSY2-70Δ‡	<b>78,071</b>	A750NSY4-70Δ‡	<b>81,446</b>	A750NSYX-70Δ‡	<b>88,725</b>

Δ Overload Relay suffix code. Select from the overload relay selection chart on page 3.6.

‡ Horsepower and line voltage suffix code. Select from page 3.74.

### Control transformer option

Contactor size	VA rating	List price adder
A9 - A40	45 ①	<b>\$ 300</b>
A9 - A40	50	<b>360</b>
A50 - A75	75	<b>435</b>
A95 - A110	100	<b>560</b>
A145 - A185	150	<b>720</b>
A210 - A300	250	<b>795</b>
A400 - A460	150	<b>720</b> ②
A580 - A750	250	<b>795</b> ②

① No primary fusing provided.

② A400 - A750 utilizes the AF wide range coil with a lower coil consumption than A210 - A300.