

# Open PSR Open type

6



Type PSR16-600-70



Type PSR30-600-70



Type PSR45-600-70

## PSR Open type

Connected In-Line Catalog number	Maximum motor current		Maximum horsepower			
	UL	IEC	208V	240V	480V	600V
<b>PSR3-600-70</b> <b>PSR3-600-81</b>	3.4	3.9	0.5	0.75	2	2
<b>PSR6-600-70</b> <b>PSR6-600-81</b>	6.1	6.8	1	1.5	3	5
<b>PSR9-600-70</b> <b>PSR9-600-81</b>	9.0	9.0	2	2	5	7.5
<b>PSR12-600-70</b> <b>PSR12-600-81</b>	11.0	12.0	3	3	7.5	10
<b>PSR16-600-70</b> <b>PSR16-600-81</b>	15.2	16.0	3	5	10	10
<b>PSR25-600-70</b> <b>PSR25-600-81</b>	24.2	25.0	7.5	7.5	15	20
<b>PSR30-600-70</b> <b>PSR30-600-81</b>	28.0	30.0	7.5	10	20	25
<b>PSR37-600-70</b> <b>PSR37-600-81</b>	34.0	37.0	10	10	25	30
<b>PSR45-600-70</b> <b>PSR45-600-81</b>	46.2	45.0	15	15	30	40

## Catalog number explanation

**PSR3 - 600 - 70**

**Maximum motor current**  
when connected in-line

**Line voltage**  
208V - 600 VAC

**Control voltage**  
70 = 100 - 240 VAC  
81 = 24 VDC