

Components

40mm, IP 65, UL Type 4

Bodies with contact block for rectilinear or angular motion heads



LS45P00B11

LS 45 P 00 B 11

Limit Switch.....LS

Casing width 40 mm3

Cable inlet

1 cable inlet for Pg 13.5 cable gland0

1 cable inlet M20 x 1.5 for ISO 20 cable gland3

1 cable inlet for 1/2" NPT5

Plastic casing.....P

Without operating head00

Contacts

111 N.O. + 1 N.C. contacts

022 N.C. contacts

202 N.O. contacts

Snap action

BZb Snap

Dependent (slow) action

LZb Slow / Simultaneous

DZb Non-overlapping late make

CZb Overlapping early make

Operating heads



LSTH41

LS T H 41

Limit Switch.....LS

Operating headT

For plastic casing 40 mm width40

References of heads

11 ... 14, 19with rectilinear movement (plain plunger, steel ball plunger or roller plunger)

31 ... 37with rectilinear movement (roller lever on steel plunger)

40with angular movement (without actuator) actuator to be ordered separately

41 ... 44with angular movement (roller lever)

50with angular movement (without actuator) actuator to be ordered separately

51 ... 54with angular movement (adjustable roller lever)

61, 62flexible lever (spring)

71, 72, 73adjustable lever (rod)

91 ... 93multidirectional angular movement (spring rod)

Separate actuators (roller lever, adjustable roller or rod levers, etc.)



LSA40X51

LS A 40 X 51

Limit Switch.....LS

Actuator (roller)A

Casing width: 40 mm40

Reference of actuators

41 ... 44non-adjustable roller lever

51 ... 54adjustable roller lever

61, 62flexible lever (spring)

71, 72, 73adjustable lever (rod)

For casing

MMetal

PPlastic

XPlastic or metal

Separate contact blocks



LSC40XC11

LS C 40 X C 11

Limit Switch.....LS

Contact blocksC

Casing width: 40 mm40

Contacts

111 N.O. + 1 N.C. contacts

022 N.C. contacts

202 N.O. contacts

Snap action:

BZb Snap

Dependent (slow) action:

LZb Slow / Simultaneous

DZb Non-overlapping late make

CZb Overlapping early make

For casing

Metal.....M

Plastic.....P

Plastic or metal.....X