

Assembled 30mm, IP 65, UL Type 4

Movement to be detected

Key translation, on end or lateral

On end



Operating head type

	Right angle key	Straight key	Plain thermoplastic plunger	Plain steel plunger
Conformity / (N.C. contact with positive opening operation)			EN 50 047	EN 50 047
Maximum actuation speed m/s	0.5	0.5	0.5	0.5
Min. force: - actuation N	18	18	9	9
- positive opening operation N	60	60	44	44

9

Snap action contacts	Catalog number	LS35P15B11	LS35P16B11	LS35P10B11	LS35P11B11
	List price	\$ 31	\$ 33	\$ 22	\$ 22
	Operation diagram				
Non-overlapping Slow action contacts	Catalog number	LS35P15D11	LS35P16D11	LS35P10D11	LS35P11D11
	List price	33	35	23	23
	Operation diagram				
Overlapping Slow action contacts	Catalog number	LS35P15C11	LS35P16C11	LS35P10C11	LS35P11C11
	List price	34	36	24	24
	Operation diagram				
Slow action contacts	Catalog number	LS35P15L02	LS35P16L02	LS35P10L02	LS35P11L02
	List price	34	36	24	24
	Operation diagram				
Slow action contacts	Catalog number	LS35P15L20	LS35P16L20	LS35P10L20	LS35P11L20
	List price	34	36	24	24
	Operation diagram				
Snap action contacts	Catalog number	LS35P15B02	LS35P16B02	LS35P10B02	LS35P11B02
	List price	34	36	24	24
	Operation diagram				
Weight (packing per unit)	kg	0.085	0.085	0.065	0.070

Approximate dimensions (mm)

