




Inductive 3 Wire DC Sensing range: 2mm

Operating distance		2mm	2mm
Catalog number		SIF2M12NV2PO SIF2M12NV2NO	SIF2M12SU2PO
List price		\$ 72.00	\$ 81.00
Sensor mounting		Shielded	Shielded
Output			
Suffix PO		PNP Normally Open	PNP Normally Open
Suffix NO		NPN Normally Open	
Operating voltage	VDC	10 – 30	10 – 60
Load current	mA	200	200
Switching frequency	Hz	1500	3000
No load supply current	mA	15	15
Voltage drop	VDC	2	2
Short circuit protection		yes	yes
Reverse polarity protection		yes	yes
Output indication		LED yellow	LED yellow
Operating temperature	°F	-13 ... +158	-13 ... +158
Protection			
IEC		IP67	IP67
Approvals			
CE		yes	yes
UL Listed		yes	yes
CSA		yes	yes
Wire size		22 AWG/0.14mm ²	22 AWG/0.14mm ²
Housing material		Nickel-plated brass	Stainless steel
Housing diameter	mm	12	12
Sensing face		Crastin	Crastin
Connection		2 m, PVC cable	2 m, PUR cable




10


Approximate dimensions



Wiring diagrams



Approximate dimensions



Wiring diagrams

