



## Transformers with CE Mark



TC60501

**Primary voltage - 550/575/ 600V**  
**Secondary voltage - 110/115/120V**



Top View

Side View

VA rating	Catalog number	List price	Output amps	Dimensions (inches • mm)					Mounting slots	Approx. wt. Lbs • kg
				A	B	C	D	E		
50	TC60501	\$ 56	0.43	3 <sup>3/8</sup> • 86	3 • 76	3 • 76	2 <sup>1/2</sup> • 64	2 <sup>1/2</sup> • 64	203 <sup>X</sup> •460 • 5.1x11.7	3.5 • 1.6
75	TC60751	63	0.65	3 <sup>1/2</sup> • 89	3 <sup>3/8</sup> • 86	3 <sup>1/4</sup> • 83	2 <sup>1/2</sup> • 64	2 <sup>13/16</sup> • 71	203 <sup>X</sup> •460 • 5.1x11.7	4.8 • 2.2
100	TC61001	76	0.87	3 <sup>5/8</sup> • 92	3 <sup>3/4</sup> • 95	3 <sup>1/2</sup> • 89	2 <sup>1/2</sup> • 64	3 <sup>1/8</sup> • 79	203 <sup>X</sup> •460 • 5.1x11.7	5.9 • 2.7
150	TC61501	100	1.30	4 • 102	4 <sup>1/2</sup> • 114	4 • 102	2 <sup>1/2</sup> • 64	3 <sup>3/4</sup> • 95	203 <sup>X</sup> •460 • 5.1x11.7	8.5 • 3.9
200	TC62001	113	1.74	4 <sup>1/2</sup> • 114	4 <sup>1/2</sup> • 114	4 • 102	3 <sup>1/2</sup> • 81	3 <sup>3/4</sup> • 95	203 <sup>X</sup> •460 • 5.1x11.7	10.6 • 4.8
250	TC62501	124	2.17	4 <sup>3/4</sup> • 121	4 <sup>1/2</sup> • 114	4 • 102	3 <sup>3/16</sup> • 81	3 <sup>3/4</sup> • 95	203 <sup>X</sup> •460 • 5.1x11.7	11.3 • 5.1
300	TC63001	137	2.61	5 <sup>3/4</sup> • 133	4 <sup>1/2</sup> • 114	4 • 102	3 <sup>3/4</sup> • 95	3 <sup>3/4</sup> • 95	203 <sup>X</sup> •460 • 5.1x11.7	13.2 • 6.0
350	TC63501	160	3.04	5 • 127	5 <sup>1/2</sup> • 133	4 • 114	3 <sup>3/4</sup> • 95	4 • 111	203 <sup>X</sup> •460 • 5.1x11.7	14.9 • 6.8
500	TC65001	178	4.35	6 • 152	5 <sup>1/4</sup> • 133	4 <sup>1/2</sup> • 114	4 <sup>3/4</sup> • 121	4 <sup>3/8</sup> • 111	.312 <sup>X</sup> •687 • 8x17.5	21.0 • 9.5
750	TC67501	264	6.52	7 <sup>3/8</sup> • 187	5 <sup>1/4</sup> • 133	4 <sup>1/2</sup> • 114	5 <sup>3/4</sup> • 146	4 <sup>3/8</sup> • 111	.312 <sup>X</sup> •687 • 8x17.5	29.8 • 13.6



Note: No integral fusing capability. Supplied with touch-safe terminal covers installed.

12



TC305021

**Primary voltage - 380/400/415V**  
**Secondary voltage - 110/220V**



Top View

Side View

VA rating	Catalog number	List price	Output amps	Dimensions (inches • mm)					Mounting slots	Approx. wt. Lbs • kg
				A	B	C	D	E		
50	TC305021	\$ 81	.46/.23	3 <sup>1/2</sup> • 89	3 • 76	3 • 76	2 <sup>1/2</sup> • 64	2 <sup>1/2</sup> • 64	203 <sup>X</sup> •460 • 5.1x11.7	3.5 • 1.6
75	TC307521	83	.68/.34	3 <sup>1/2</sup> • 89	3 <sup>3/8</sup> • 86	3 <sup>1/4</sup> • 83	2 <sup>1/2</sup> • 64	2 <sup>13/16</sup> • 71	203 <sup>X</sup> •460 • 5.1x11.7	4.8 • 2.2
100	TC310021	94	.91/.46	3 <sup>5/8</sup> • 92	3 <sup>3/4</sup> • 95	3 <sup>1/2</sup> • 89	2 <sup>1/2</sup> • 64	3 <sup>1/8</sup> • 79	203 <sup>X</sup> •460 • 5.1x11.7	5.9 • 2.7
150	TC315021	120	1.37/.69	4 • 102	4 <sup>1/2</sup> • 114	4 • 102	2 <sup>1/2</sup> • 64	3 <sup>3/4</sup> • 95	203 <sup>X</sup> •460 • 5.1x11.7	8.5 • 3.9
200	TC320021	133	1.82/.91	4 <sup>1/2</sup> • 114	4 <sup>1/2</sup> • 114	4 • 102	3 <sup>1/2</sup> • 81	3 <sup>3/4</sup> • 95	203 <sup>X</sup> •460 • 5.1x11.7	10.6 • 4.8
250	TC325021	154	2.28/1.14	4 <sup>3/4</sup> • 121	4 <sup>1/2</sup> • 114	4 • 102	3 <sup>3/16</sup> • 81	3 <sup>3/4</sup> • 95	203 <sup>X</sup> •460 • 5.1x11.7	11.3 • 5.1
300	TC330021	178	2.72/1.36	5 <sup>1/4</sup> • 133	4 <sup>1/2</sup> • 114	4 • 102	3 <sup>3/4</sup> • 95	3 <sup>3/4</sup> • 95	203 <sup>X</sup> •460 • 5.1x11.7	13.2 • 6.0
350	TC335021	193	3.18/1.59	5 <sup>1/2</sup> • 140	4 <sup>1/2</sup> • 114	4 • 102	4 <sup>1/16</sup> • 103	3 <sup>3/4</sup> • 95	203 <sup>X</sup> •460 • 5.1x11.7	15.2 • 6.9
500	TC350021	210	4.55/2.27	6 • 152	5 <sup>1/4</sup> • 133	4 <sup>1/2</sup> • 114	4 <sup>3/4</sup> • 121	4 <sup>3/8</sup> • 111	.312 <sup>X</sup> •687 • 8x17.5	21.0 • 9.5
750	TC375021	260	6.82/3.41	7 <sup>3/8</sup> • 187	5 <sup>1/4</sup> • 133	4 <sup>1/2</sup> • 114	5 <sup>3/4</sup> • 146	4 <sup>3/8</sup> • 111	.312 <sup>X</sup> •687 • 8x17.5	29.8 • 13.6

Note: No integral fusing capability. Supplied with touch-safe terminal covers installed.