

Technical data

S500

Item	S500-B, C, D	S500-K
Approvals:		
UL	1077	1077
CSA	C22.2 - No.235	C22.2 - No. 235
VDE	0641/6.78	0641/6.78
IEC	947-2	—
No. of poles:	1,2,3, +N, +NA	1,2,3, +N, +NA
Tripping characteristic:	B.C.D.	K
Rated currents:	6 to 63A	0.1 to 45A
Rated voltage:		
UL/CSA single pole	277VAC	277VAC
UL/CSA multi pole	600VAC	600VAC
IEC single pole	690VAC	690VAC
Rated interrupting capacity:		
Single pole	6-25A – 30KA/240VAC 14KA/277VAC	0.15-25A – 30KA/240VAC 14KA/277VAC
	32-63A – 18KA/240VAC 14KA/277VAC	26-45A – 18KA/240VAC 14KA/277VAC
Multi-pole	6-63A – 14KA/480VAC 6KA/600VAC	0.15-45A – 14KA/480VAC 6KA/600VAC
Frequency:	50/60 Hz	50/60Hz
Mounting position:	optional	optional
Standard mounting:	35mm DIN rail	35mm DIN rail
Terminals:	Conductors from 16-4AWG (1-25sq mm)	Conductors from 16-4AWG (1-25sq mm)
Service life at rated load:	20,000 operations	20,000 operations
Calibration temperature:	40°C	40°C

Item	S500UC-B, K
Approvals:	
UL	1077
CSA	C22.2
VDE	0660
No. of poles:	1,2,3, 4
Tripping characteristic:	B, K
Rated currents:	B: 6 to 63A K: 0.15 to 45A
Rated voltage:	
UL single pole	277VAC/250VDC
UL multi pole	600VAC/600VDC
IEC multi pole	690VAC/750VDC
Rated interrupting capacity:	
	B single pole:
	6 – 25A 18KA/240VAC 14KA/277VAC 30KA/250VDC
	32 – 63A 30KA/240VAC 14KA/277VAC 30KA/250VDC
	B two-pole:
	6 – 63A 14KA/480VAC 6KA/600VAC 30KA/500VDC
	B three-pole:
	6 – 63A 14KA/480VAC 6KA/600VAC 30KA/600VDC
	K single pole:
	0.15 – 25A 30KA/240VAC 14KA/277VAC 30KA/250VDC
	32 – 45A 18KA/240VAC 14KA/277VAC 30KA/250VDC
	K two-pole:
	0.15 – 45A 14KA/480VAC 6KA/600VAC 30KA/500VDC
	K three-pole:
	0.5 – 45A 14KA/480VAC 6KA/600VAC 30KA/600VDC
Frequency:	50/60Hz
Mounting position:	optional
Standard mounting:	35mm DIN-rail
Terminals:	Conductors from 16 to 4AWG (1-25sq mm)
Service life at rated load:	20,000 operations