



# S4 250A, 600VAC

## Magnetic only (MCP)

All S4 magnetic only breakers utilize the electronic PR211 trip unit with an adjustable range of 1.5 to 12 times frame rating. Both two and three pole MCPs are 600VAC rated.

Type	Amps	Interruption capacity	Adjustment range	2 pole 600VAC catalog number	List price	3 pole 600VAC catalog number	List price
S4N	100 250	240VAC 65kA 480VAC 25kA 600VAC 18kA	150 – 1200A 375 – 3000A	S4N100MW-2 S4N250MW-2	<b>\$ 1073</b>	S4N100MW S4N250MW	<b>\$ 1347</b>
S4H	100 250	240VAC 150kA 480VAC 65kA 600VAC 22kA	150 – 1200A 375 – 3000A	S4H100MW-2 S4H250MW-2	<b>2572</b>	S4H100MW S4H250MW	<b>3030</b>
S4L	100 250	240VAC 200kA 480VAC 100kA 600VAC 35kA	150 – 1200A 375 – 3000A	S4L100MW-2 S4L250MW-2	<b>3159</b>	S4L100MW S4L250MW	<b>3950</b>

## Molded case switch

Type	Interruption capacity ②	Amps	Magnetic trip	3 pole catalog number	List price
S4H-D	240VAC 150kA 480VAC 65kA 600VAC 22kA	250	3000A	S4H250DW	<b>\$ 1215</b>

## Neutral GF current transformer (required for 4 wire GF systems)

Amps	Catalog number	List price
100	K4NCT-100	<b>\$ 250</b>
250	K4NCT-250	

## Connection options

Type	Wire range	Amps ①	Set of 2 catalog number	List price	Set of 3 catalog number	List price
CU/AL front lugs	14AWG – 1/0	100	K4TB-2	<b>\$ 4</b>	K4TB	<b>\$ 6</b>
CU/AL front lugs	2AWG – 4/0	150	K4TC-2	<b>4</b>	K4TC	<b>6</b>
CU/AL front lugs	4AWG – 300kcmil	225	K4TD-2	<b>10</b>	K4TD	<b>15</b>
CU/AL front lugs	6AWG – 350kcmil	250	K4TE-2	<b>20</b>	K4TE	<b>30</b>
CU front lugs (saddle) CU rear lugs	14AWG – 250kcmil	250	—	—	Set of 6 catalog number	<b>30</b>
	6AWG – 250kcmil	250	—	—	K4TES K4TER	
Extended front bar	—	250	—	—	K4ET-250	<b>46</b>

① Suggested lugs for a circuit breaker up to the amps shown. Cable size and type determine maximum amperage.

② With fuse or MCCB protected circuit.