



S5 400A, 600VAC

Magnetic only (MCP)

All S5 magnetic only breakers utilize the electronic PR211 trip unit with an adjustable range of 1.5 to 12 times frame rating. Both two and three pole MCP's are 600VAC rated.

Type	Amps	Interruption capacity		Adjustment range	2 pole 600VAC catalog number	List price	3 pole 600VAC catalog number	List price
S5N	400	240 VAC 480VAC 600VAC	65kA 35kA 22kA	600 – 4800A	S5N400MW-2	\$ 1798	S5N400MW	\$ 2151
S5H	400	240VAC 480VAC 600VAC	150kA 65kA 22kA	600 – 4800A	S5H400MW-2	3285	S5H400MW	3654
S5L	400	240VAC 480VAC 600VAC	200kA 100kA 35kA	600 – 4800A	S5L400MW-2	3945	S5L400MW	4733

Molded case switch

Switch	Interruption capacity ③		Amps	Magnetic trip	3 pole catalog number	List price
S5H-D	240VAC 480VAC 600VAC 600VDC	150kA 65kA 22kA 50kA	400A	5000A	S5H400DW	\$ 1994

Neutral GF current transformer (required for 4 wire GF systems)

Amps	Catalog number	List price
400	K5NCT-400	\$ 250

Connection options

Type	Wire range	Amps ②	Set of 2 catalog number	List price	Set of 3 catalog number	List price
CU/AL front lugs	250kcmil – 500kcmil	300	K5TF-2	\$ 30	K5TF K5TG ①	\$ 45
CU/AL front lugs	(2) 3/0 – 250kcmil	400	K5TG-2 ①			
CU front lugs (saddle) CU rear lugs Extended front bar	250kcmil – 500kcmil	400	—	—	Set of 6 catalog number K5TGS K5TGR K5ET-400	90
	250kcmil – 500kcmil	400	—	—		
	—	400	—	—		

15

① Including lug cover.

② Suggested lugs for a circuit breaker up to amps shown. Cable size and type determine maximum amperage.

③ With fuse or MCCB protected circuit.