



S7 1200A, 600V

Magnetic only (MCP)

All S7 magnetic only breakers utilize the electronic PR211 trip unit with an adjustable range of 1.5 to 12 times frame rating. Both two and three pole MCPs are 600VAC rated.

Type	Amps	Interruption capacity		Adjustment range	2 pole catalog number	List price	3 pole catalog number	List price
S7H	1000 1200	240VAC 480VAC 600VAC	100kA 65kA 50kA	1500 – 12,000A 1800 – 14,400A	S7H1000MW-2 S7H1200MW-2	\$ 6959	S7H1000MW S7H1200MW	\$ 7724

Molded case switches

Type	Interruption capacity ②		Amps	Magnetic trip	3 pole catalog number	List price
S7H-D	240VAC 480VAC 600VAC 600VDC	100kA 65kA 50kA 12kA	1000 1200	20,000A 20,000A	S7H1000DW S7H1200DW	\$ 7300
Non-UL, switches without overcurrent protection	Withstand rating 600VAC 25kA		1000 1250	— —	S7D1000W S7D1250W	

Neutral current transformer (required for 4 wire GF systems)

Amps	Catalog number	List price
1000 1200	K7NCT-1000 K7NCT-1200	\$ 250

Connection options

Type	Wire range	Amps ①	Set of 2 catalog number	List price	Set of 3 catalog number	List price
CU/AL front lugs	(4) 4/0 – 500kcmil	1200	K7TK-2	\$ 120	K7TK	\$ 180
Extended front bar	—	1200	—	—	Set of 6 catalog number K7ET-1250	240

① Suggested lugs for a circuit breaker up to amps shown. Cable size and type determine maximum amperage.
② With fuse or MCCB protected circuit.