

External accessories

Flange handle operators

S1 – S6



K7FHD-HS12

Flange handle

Solid shaft linkage

Breaker	NEMA type	Complete handle kit	List price	Mechanism only	List price	Shaft only	Shaft length	List price	Handle only	List price
S1	1,3R,12	K2FHD-12S12	\$ 240	K2FHD-M	\$ 128	K7FHD-S12	12	\$ 19	K7FHD-HS12	\$ 93
		K2FHD-17S12	248			K7FHD-S17	17	27		
		K2FHD-22S12	255			K7FHD-S22	22.5	34		
4, 4X	K2FHD-12S4	280	K7FHD-S12	12	19					
		K2FHD-17S4		288	K7FHD-S17	17	27			
		K2FHD-22S4		295	K7FHD-S22	22.5	34			
S3	1,3R,12	K3FHD-12S12	240	K3FHD-M	128	K7FHD-S12	12	19	K7FHD-HS12	93
		K3FHD-17S12	248			K7FHD-S17	17	27		
		K3FHD-22S12	255			K7FHD-S22	22.5	34		
4, 4X	K3FHD-12S4	280	K7FHD-S12	12	19					
		K3FHD-17S4		288	K7FHD-S17	17	27			
		K3FHD-22S4		295	K7FHD-S22	22.5	34			
S4	1,3R,12	K4FHD-12S12	240	K4FHD-M	128	K7FHD-S12	12	19	K7FHD-HS12	93
		K4FHD-17S12	248			K7FHD-S17	17	27		
		K4FHD-22S12	255			K7FHD-S22	22.5	34		
4, 4X	K4FHD-12S4	280	K7FHD-S12	12	19					
		K4FHD-17S4		288	K7FHD-S17	17	27			
		K4FHD-22S4		295	K7FHD-S22	22.5	34			
S5	1,3R,12	K5FHD-12S12	240	K5FHD-M	128	K7FHD-S12	12	19	K7FHD-HS12	93
		K5FHD-17S12	248			K7FHD-S17	17	27		
		K5FHD-22S12	255			K7FHD-S22	22.5	34		
4, 4X	K5FHD-12S4	280	K7FHD-S12	12	19					
		K5FHD-17S4		288	K7FHD-S17	17	27			
		K5FHD-22S4		295	K7FHD-S22	22.5	34			
S6	1,3R,12	K6FHD-12S12	523	K6FHD-M	411	K7FHD-S12	12	19	K7FHD-HS12	93
		K6FHD-17S12	531			K7FHD-S17	17	27		
		K6FHD-22S12	538			K7FHD-S22	22.5	34		
4, 4X	K6FHD-12S4	563	K7FHD-S12	12	19					
		K6FHD-17S4		571	K7FHD-S17	17	27			
		K6FHD-22S4		578	K7FHD-S22	22.5	34			

Available as complete kits including flange handle, shaft and breaker operating mechanism. Mechanism mounts directly onto breaker and shaft can be cut to the desired length for the breaker enclosure. Door is interlocked with the handle when the breaker is in the closed (ON) position; handles include interlock defeater for emergency override. Handle can be padlocked in the open (OFF) position. Can be field converted for left hand mounting.

Door hardware kits — Solid shaft linkage & S1 - S2 Cable operated

Item	Catalog number	List price
Door hardware kit, right hand, 2 point latch for enclosures less than 40 inches high	FH-DHK	\$ 150
Roller for 3 point latch, add to FH-DHK	FH-3RL	30

Enclosure depths

Minimum

Breaker	Depth (inches)
S1	8
S3 - S5	10
S6	11

Maximum

For maximum depth, add 4 inches to the shaft length

① Cable not included.