

Non-automatic air circuit breakers

Fixed switches (without trip unit & c.t.s.), 3 pole UL

Fixed switches

Circuit breaker type	Frame amps	Interrupting ratings kA, 480V	Manually operated	Electrically operated	Set of three vertical terminals
E1B-A/MS08	800	42	\$ 5086	\$ 7447	\$ 644
E1B-A/MS12	1200	42	5592	7953	644
E2N-A/MS12	1200	50	6090	8451	690
E3S-A/MS12	1200	65	6944	9305	790
E2B-A/MS16	1600	42	6142	8503	690
E2N-A/MS16	1600	50	7353	9714	690
E3S-A/MS16	1600	65	7961	10,322	790
E3N-A/MS20	2000	50	8196	10,557	790
E3S-A/MS20	2000	65	9217	11,578	790
E3N-A/MS25	2500	50	12,942	15,303	790
E3S-A/MS25	2500	65	14,615	16,976	790
E4S-A/MS32	3200	65	18,733	21,094	1664
E4H-A/MS32	3200	85	19,197	21,558	1664
E4S-A/MS36	3600	65	21,570	23,931	1664
E4H-A/MS36	3600	85	24,933	27,294	1664
E6H-A/MS40	4000	85	28,946	31,307	2783
E6H-A/MS50	5000	85	40,639	43,000	2783

Standard features – manually operated UL switch

- Rear horizontal terminals
- Manual mechanical close and open pushbuttons
- CB open/closed mechanical indicator
- Spring charged/discharged mechanical indicator
- Lifting plates
- Terminal box