


# Non-automatic air circuit breakers

## Fixed switches (without trip unit & c.t.s.), 4 pole

### UL



#### Fixed switches

Circuit breaker type	Frame amps	Interrupting ratings kA, 480V	Manually operated	Electrically operated	Set of four vertical terminals
E1B-A/MS08	800	42	\$ 6866	\$ 9227	\$ 644
E1B-A/MS12	1200	42	7549	9910	644
E2N-A/MS12	1200	50	8222	10,583	690
E3S-A/MS12	1200	65	9374	11,735	790
E2B-A/MS16	1600	42	8292	10,653	690
E2N-A/MS16	1600	50	9927	12,288	690
E3S-A/MS16	1600	65	10,747	13,108	790
E3N-A/MS20	2000	50	11,065	13,426	790
E3S-A/MS20	2000	65	12,443	14,804	790
E3N-A/MS25	2500	50	17,472	19,833	790
E3S-A/MS25	2500	65	19,730	22,091	790
E4S-A/MS32	3200	65	25,290	27,651	1664
E4H-A/MS32	3200	85	25,916	28,277	1664
E4S-A/MS36	3600	65	29,120	31,481	1664
E4H-A/MS36	3600	85	33,660	36,021	1664
E6H-A/MS40	4000	85	39,077	41,438	2783
E6H-A/MS50	5000	85	54,863	57,224	2783

#### Standard features – manually operated UL switch

- Rear horizontal terminals
- Manual mechanical close and open pushbuttons
- CB open/closed mechanical indicator
- Spring charged/discharged mechanical indicator
- Lifting plates
- Terminal box

#### Neutral pole rating

- E1 – E3 = 100% rating
- E4 – E6 = 50% rating