

Non-automatic air circuit breakers

Withdrawable switches (without trip unit & c.t.s.), 3 pole UL

Withdrawable switches

Circuit breaker type	Frame amps	Interrupting ratings kA, 480V	Moving part only		Fixed part only	
			Manually operated	Electrically operated	RH terminals	Set of three vertical terminals
E1B-A/MS08	800	42	\$ 5654	\$ 8015	\$ 2281	\$ 644
E1B-A/MS12	1200	42	6646	9007	2281	644
E2N-A/MS12	1200	50	7085	9446	2400	690
E3S-A/MS12	1200	65	7384	9745	2925	790
E2B-A/MS16	1600	42	7591	9952	2400	690
E2N-A/MS16	1600	50	8754	11,115	2400	690
E3S-A/MS16	1600	65	9095	11,456	2925	790
E3N-A/MS20	2000	50	9550	11,911	2925	790
E3S-A/MS20	2000	65	10,864	13,225	2925	790
E3N-A/MS25	2500	50	15,931	18,292	2925	790
E3S-A/MS25	2500	65	18,479	20,840	2925	790
E4S-A/MS32	3200	65	21,431	23,792	6259	1664
E4H-A/MS32	3200	85	22,078	24,439	6259	1664
E4S-A/MS36	3600	65	24,494	26,855	6259	1664
E4H-A/MS36	3600	85	28,496	30,857	6259	1664
E6H-A/MS40	4000	85	32,094	34,455	7398	2783
E6H-A/MS50	5000	85	43,820	46,181	7398	2783

Standard features – manually operated switch

Moving part

- Manual mechanical close and open pushbuttons
- Circuit breaker open/closed mechanical indicator
- Spring charged/discharged mechanical indicator
- Lifting plates
- Racking device with closed door
- Circuit breaker racking position indicator
- Sliding contacts
- Fail-safe device (not available with YU)

Standard features – manually operated switch

Fixed part

- Safety shutters
- Rear horizontal terminals
- Sliding contacts
- Anti-insertion lock
- Ground connection