

Withdrawable breakers, 3 poles IEC

Withdrawable breakers

Circuit breaker type	Frame amps	Interrupting ratings kA, 415V	Moving part only		Fixed part		
			Manually operated	Electrically operated	RH terminals	Set of three vertical terminals	Set of three front terminals
E1B08	800	40	\$ 6501	\$ 8862	\$ 2281	\$ 644	\$ 367
E1B12	1250	40	7757	10,118	2281	644	367
E2N12	1250	65	8626	10,987	2400	690	888
E3S12	1250	75	8760	11,121	2925	790	1232
E3H12	1250	100	8897	11,258	2925	790	1232
E2L12	1250	130	12,180	14,541	2400	690	888
E2B16	1600	40	9097	11,458	2400	690	888
E2N16	1600	65	10,234	12,595	2400	690	888
E3S16	1600	75	10,674	13,035	2925	790	1232
E3H16	1600	100	11,100	13,461	2925	790	1232
E2L16	1600	130	15,920	18,281	2400	690	888
E2B20	2000	40	10,987	13,348	2400	690	888
E2N20	2000	65	11,182	13,543	2400	690	888
E3S20	2000	75	11,361	13,722	2925	790	1232
E3H20	2000	100	13,256	15,617	2925	790	1232
E3L20	2000	130	17,817	20,178	2925	790	888
E3N25	2500	65	15,220	17,581	2925	790	1232
E3S25	2500	75	17,896	20,257	2925	790	1232
E3H25	2500	100	19,528	21,889	2925	790	1232
E3L25	2500	130	22,892	25,253	2925	790	1232
E3N32	3200	65	22,337	24,698	2925	790	1232
E3S32	3200	75	23,340	25,701	2925	790	1232
E3H32	3200	100	23,724	26,085	2925	790	1232
E4H32	3200	100	23,842	26,203	6259	1664	1696
E6V32	3200	150	38,539	40,900	7398	2783	2464
E4S40	4000	75	30,399	32,760	6259	1664	1696
E4H40	4000	100	34,540	36,901	6259	1664	1696
E6V40	4000	150	45,340	47,701	7398	2783	2464
E6H50	5000	100	45,541	47,902	7398	2783	2464
E6V50	5000	150	53,341	55,702	7398	2783	2464
E6H63	6300	100	64,163	66,524	7398	2783	2464
E6V63	6300	150	78,427	80,788	7398	2783	2464

Standard features – electrically operated breaker

Moving part

- PR111 trip unit with LI protection functions
- Spring charging motor
- Shunt trip
- Closing coil
- Manual mechanical close and open pushbuttons
- CB open/closed mechanical indicator
- Spring charged/discharged mechanical indicator
- 2NO & 2NC auxiliary contacts for open-closed position indication
- Lifting plates
- Current transformers
- Racking device with closed door
- Circuit breaker racking position indicator
- Sliding contacts

Standard features – electrically operated breaker

Fixed part

- Safety shutters
- Rear horizontal terminals
- Sliding contacts
- Anti-insertion lock
- Ground connection