

Withdrawable breakers, 3 pole UL

Withdrawable breakers

Circuit breaker type	Frame amps	Interrupting ratings kA, 480V	Moving part only		Fixed part only	
			Manually operated	Electrically operated	RH terminals	Set of three vertical terminals
E1B-A08	800	42	\$ 7383	\$ 9744	\$ 2281	\$ 644
E1B-A12	1200	42	8375	10,736	2281	644
E2N-A12	1200	50	8814	11,175	2400	690
E3S-A12	1200	65	9220	11,581	2925	790
E3H-A12	1200	85	9633	11,994	2925	790
E3V-A12	1200	100	10,596	12,957	2925	790
E2B-A16	1600	42	9320	11,681	2400	690
E2N-A16	1600	50	10,483	12,844	2400	690
E3S-A16	1600	65	10,931	13,292	2925	790
E3H-A16	1600	85	11,445	13,806	2925	790
E3V-A16	1600	100	12,590	14,951	2925	790
E3N-A20	2000	50	11,386	13,747	2925	790
E3S-A20	2000	65	12,700	15,061	2925	790
E3H-A20	2000	85	14,262	16,623	2925	790
E3V-A20	2000	100	15,688	18,049	2925	790
E3N-A25	2500	50	17,767	20,128	2925	790
E3S-A25	2500	65	20,315	22,676	2925	790
E3H-A25	2500	85	22,622	24,983	2925	790
E3V-A25	2500	100	24,884	27,245	2925	790
E4S-A32	3200	65	23,800	26,161	6259	1664
E4H-A32	3200	85	24,447	26,808	6259	1664
E4V-A32	3200	100	25,863	28,224	6259	1664
E4S-A36	3600	65	26,863	29,224	6259	1664
E4H-A36	3600	85	30,865	33,226	6259	1664
E4V-A36	3600	100	31,948	34,309	6259	1664
E6H-A40	4000	85	34,676	37,037	7398	2783
E6V-A40	4000	125	46,570	48,931	7398	2783
E6H-A50	5000	85	46,402	48,763	7398	2783
E6V-A50	5000	125	57,078	59,439	7398	2783

Standard features – electrically operated breaker

Moving part

- PR111 trip unit with LI protection feature
- Spring charging motor
- Shunt trip
- Closing coil
- Manual mechanical close and open pushbuttons
- CB open/closed mechanical indicator
- Spring charged/discharged mechanical indicator
- 2NO & 2NC auxiliary contacts for open-closed position indication
- Lifting plates
- Current transformers
- Racking device with closed door
- Circuit breaker racking position indicator
- Sliding contacts
- Fail safe device (not available with YU)

Standard features – electrically operated breaker

Fixed part

- Safety shutters
- Rear horizontal terminals
- Sliding contacts
- Anti-insertion lock
- Ground connection