

16A – 100A, Base & DIN rail mounted Handles & shafts

Disconnect
switches
Non-fusible



Pistol handles — for use with shafts $\square .20 \times .20"$ ($\square 5 \times 5 \text{ mm}$)

| UL/NEMA type | IEC type | Color | Marking | Length inches/mm | Defeatable | Padlockable | Weight (lbs.) | Catalog number | List price |
|--------------|----------|---------|--------------|------------------|------------|-------------|---------------|----------------|------------|
| 1,3R,12 | IP65 | Black | O/I & Off/On | 1.8/45 | Yes | Yes | 0.28 | OHB45J5 | \$ 70 |
| 1,3R,12 | IP65 | Red/Yel | O/I & Off/On | 1.8/45 | Yes | Yes | 0.28 | OHY45J5 | 70 |
| 1,3R,12 | IP65 | Black | O/I & Off/On | 2.6/65 | Yes | Yes | 0.29 | OHB65J5 | 80 |
| 1,3R,12 | IP65 | Red/Yel | O/I & Off/On | 2.6/65 | Yes | Yes | 0.29 | OHY65J5 | 80 |
| 1,3R,12,4,4X | IP66 | Black | O/I & Off/On | 2.6/65 | Yes | Yes | 0.29 | OHB65L5 | 120 |
| 1,3R,12,4,4X | IP66 | Red/Yel | O/I & Off/On | 2.6/65 | Yes | Yes | 0.29 | OHY65L5 | 120 |

Shafts — for use with pistol handles $\square .20 \times .20"$ ($\square 5 \times 5 \text{ mm}$)

| Shaft length (inches/mm) | Mounting depth ^① (inches) | | | Weight (lbs.) | Catalog number | List price |
|--------------------------|--------------------------------------|------------------|-----------------------------|---------------|----------------|------------|
| | OT16E3 OT25E3 OT32E3 | OT45E3 OT63E3 | OT30E3 OT60E3 OT100E3 | | | |
| 5.9/150 | 6.2 – 6.7 | 6.9 – 7.4 | 6.4 – 7.4 | 0.07 | OXP5X150 | \$ 14 |
| 6.7/170 | 7.0 – 7.5 | 7.7 – 8.1 | 7.2 – 8.1 | 0.08 | OXP5X170 | 16 |
| 10.4/265 | 10.7 – 11.3 | 11.4 – 11.9 | 10.9 – 11.9 | 0.12 | OXP5X265 | 18 |
| 15.8/400 | 16.0 – 16.6 | 16.8 – 17.2 | 16.2 – 17.2 | 0.18 | OXP5X400 | 30 |
| 19.7/500 | 20.0 – 20.5 | 20.7 – 21.1 | 20.1 – 21.1 | 0.23 | OXP5X500 | 42 |

Twisted shafts — Rotates handle 45° $\square .20 \times .20"$ ($\square 5 \times 5 \text{ mm}$)

| Shaft length (inches/mm) | Mounting depth ^① (inches) | | | Weight (lbs.) | Catalog number | List price |
|--------------------------|--------------------------------------|------------------|-----------------------------|---------------|----------------|------------|
| | OT16E3 OT25E3 OT32E3 | OT45E3 OT63E3 | OT30E3 OT60E3 OT100E3 | | | |
| 5.9/150 | 6.2 – 6.7 | 6.9 – 7.4 | 6.4 – 7.4 | 0.07 | OXP5X150-45 | \$ 14 |
| 6.7/170 | 7.0 – 7.5 | 7.7 – 8.1 | 7.2 – 8.1 | 0.08 | OXP5X170-45 | 16 |
| 10.4/265 | 10.7 – 11.3 | 11.4 – 11.9 | 10.9 – 11.9 | 0.12 | OXP5X265-45 | 18 |
| 15.8/400 | 16.0 – 16.6 | 16.8 – 17.2 | 16.2 – 17.2 | 0.18 | OXP5X400-45 | 30 |
| 19.7/500 | 20.0 – 20.5 | 20.7 – 21.1 | 20.1 – 21.1 | 0.23 | OXP5X500-45 | 42 |

Replacement knob — mounts directly to switch; no shaft necessary

| UL/NEMA Type | Color | For use on: | Length (inches) | Padlockable | Catalog number | List price |
|--------------|-------|--------------------|-----------------|------------------|----------------|----------------|
| 1 | Red | OT16, OT25, OT32 | 1.0 | — | CXBY68135 | \$ 8 |
| 1 | Red | OT30, OT45 – OT100 | 1.4 | — | CXBY68306 | 12 |
| 1 | Red | OT30, OT45 – OT100 | 1.6 | Yes ^② | CXBY68419/1 | 14 |
| Metal collar | | OT16 – OT100 | — | — | OTZS1 | 13 |
| Set screw | | OT16 – OT100 | — | — | FLSWM5X8AY | 2 ^③ |

Modular adapter cover — for OT16, OT25, OT32

| Item | For use | Length on: | Padlockable (inches) | Catalog number | List price |
|---------------|-----------------|------------|----------------------|----------------|------------|
| Adapter cover | OT16, OT25 OT32 | — | Yes | OHY7 | \$ 28 |

A padlock can be used with the adapter cover.

① Mounting depth is the distance from the outside of door to the disconnect switch mounting plate. Shaft can be cut to desired length.
 ② .1875" (3/16") diameter shackle required.
 ③ Set screw FLSWM5X8AY needed with replacement knobs CXBY__.