

Approximate dimensions for enclosed 6-pole transfer & mechanical interlock switches 16A – 3150A NF

Non-Fusible

Frame size	Enclosure type	H height	W width	D depth	MH mtg. height	MW mtg. width	Weight (lbs.)
OT16 OT25 OT32	1	6.0	6.0	4.0	3.0	5.0	4.0
	3R	6.0	6.0	4.0	6.75	4.0	4.0
	4	6.0	6.0	4.0	6.75	4.0	4.0
	4X SS	6.0	6.0	4.0	6.75	4.0	4.0
	4X Plastic	6.0	6.0	5.9	6.75	4.0	4.0
	12	6.0	6.0	4.0	6.75	4.0	4.0
	IP65 (A)	5.9	5.1	3.4	5.35	4.57	1.2
	IP65 (B)	–	–	–	–	–	–
OT45 OT63	1	10.0	8.0	6.0	7.0	7.0	6.0
	3R	10.0	8.0	6.0	10.75	6.0	6.0
	4	10.0	8.0	6.0	10.75	6.0	6.0
	4X SS	10.0	8.0	6.0	10.75	6.0	6.0
	4X Plastic	10.0	8.0	7.9	10.75	6.0	6.0
	12	10.0	8.0	6.0	10.75	6.0	6.0
	IP65 (A)	7.9	5.7	4.0	7.18	5.10	1.5
	IP65 (B)	–	–	–	–	–	–
OT30 OT60 OT100	1	10.0	8.0	6.0	7.0	7.0	9.0
	3R	10.0	8.0	6.0	10.75	6.0	9.0
	4	10.0	8.0	6.0	10.75	6.0	9.0
	4X SS	10.0	8.0	6.0	10.75	6.0	9.0
	4X Plastic	10.0	8.0	7.9	0.0	0.0	9.0
	12	10.0	8.0	6.0	10.75	6.0	9.0
	IP65 (A)	–	–	–	–	–	–
	IP65 (B)	–	–	–	–	–	–
OT160	1	14.0	12.0	8.0	11.0	9.0	20
	3R	14.0	12.0	8.0	14.75	10.0	20
	4	14.0	12.0	8.0	14.75	10.0	20
	4X SS	14.0	12.0	8.0	14.75	10.0	20
	4X Plastic	14.0	12.0	8.0	0.0	0.0	20
	12	14.0	12.0	8.0	14.75	10.0	20

- ① Please consult factory; enclosures can be custom sized to suit specific needs
 ② Enclosure is free standing.

Frame size	Enclosure type	H height	W width	D depth	MH mtg. height	MW mtg. width	Weight (lbs.)
OETL-NF175 OETL-NF200A	3R	24.0	24.0	10.0	25.5	22.5	60
	4	24.0	24.0	10.0	25.5	22.5	60
	4X SS	24.0	24.0	10.0	25.5	22.5	60
	4X Plastic	24.0	16.0	10.0	25.5	22.5	60
	12	24.0	24.0	10.0	25.5	22.5	60
OETL-NF400 OETL-NF600A	1	48.0	36.0	12.0	49.5	34.5	160
	3R	48.0	36.0	12.0	49.5	34.5	160
	4	48.0	36.0	12.0	49.5	34.5	160
	4X SS	48.0	36.0	12.0	49.5	34.5	160
	4X Plastic	①	①	①	①	①	①
12	48.0	36.0	12.0	49.5	34.5	160	
OETL-NF800A OETL-NF1200	1	60.0	36.0	12.0	61.5	34.5	240
	3R	60.0	36.0	12.0	61.5	34.5	240
	4	60.0	36.0	12.0	61.5	34.5	240
	4X SS	60.0	36.0	12.0	61.5	34.5	240
	4X Plastic	①	①	①	①	①	①
	12	60.0	36.0	12.0	61.5	34.5	240
OETL-NF1600 OETL-NF2000 OETL-NF3150	1	90.0	36.0	24.0	②	②	600
	3R	90.0	36.0	24.0	②	②	600
	4	①	①	①	①	①	①
	4X SS	①	①	①	①	①	①
	4X Plastic	①	①	①	①	①	①
	12	90.0	36.0	24.0	②	②	600

