

Disconnect switches
Non-fusible

16A – 100A, Base & DIN rail mounted 3 Pole transfer switches

For a complete assembly,
please select one of each:

- 1 switch
- 1 handle
- 1 shaft




OT45E3



OXS5X180



OHB_J5



OT45E3C



OHB2AJE011



OHB_J5



OHY_J5



OXS5X_

16 – 100 Amp – 600V, 3 Pole transfer switches ①

UL general purpose amp rating	IEC AC21 amp rating	Maximum horsepower ratings						Terminal lugs		Shaft size (mm)	Catalog number	List price
		Single phase		Three phase				Wire size	Wire type			
		120V	240V	200V	240V	480V	600V					
16	16	1	2	3	5	10	10	#18 – 8	Cu	5	OT16E3C	\$ 258
25	25	1.5	3	7.5	7.5	15	20				OT25E3C	270
40	40	2	5	10	10	20	25				OT32E3C	288
60	63	2	5	15	15	30	30	#14 – 1	Cu	5	OT45E3C	328
80	80	2	5	20	20	40	40				OT63E3C	368
30	40	2	5	10	10	20	30	#14 – 4	Cu	5	OT30E3C	428
60	63	3	7.5	20	20	40	40				OT60E3C	478
100	115	5	15	25	30	50	50				OT100E3C	514

UL 508
UL 98

Selector handles — 5mm, for use with transfer switches; marked I/ON - O/OFF - II/ON

UL/NEMA type	IEC type	Color	Defeatable	Padlockable	Weight (lbs.)	Catalog number	List price
1, 3R, 12	IP65	Black Red/Yel	Yes	Yes	0.16	OHB2AJE011 OHY2AJE011	\$ 40

Shafts for selector handles —5mm, for use with transfer switches

Shaft length (inches/mm)	Mounting depth ^② (inches)			Weight (lbs)	Shaft size (mm)	Catalog number	List price
	OT16E3C OT25E3C OT32E3C	OT45E3C OT63E3C	OT30E3C OT60E3C OT100E3C				
3.3/85	3.6 - 4.3	4.4 - 5.0	3.9 - 4.9	0.04	5	OXS5X85	\$ 4
4.1/105	4.4 - 5.1	5.1 - 5.8	4.7 - 5.7	0.04		OXS5X105	4
4.7/120	5.0 - 5.8	5.7 - 6.4	5.3 - 6.3	0.05		OXS5X120	4
5.1/150	5.4 - 6.1	6.1 - 6.8	5.6 - 6.7	0.05		OXS5X150	6
7.1/180	7.4 - 8.1	8.1 - 8.7	7.6 - 8.6	0.08		OXS5X180	6
9.8/250	10.1 - 10.8	10.9 - 11.5	10.4 - 11.4	0.1		OXS5X250	12
13/330	13.3 - 14.0	14.0 - 14.7	13.5 - 14.5	0.14		OXS5X330	20

Pistol handles — 5mm, for use with transfer switches; marked I/ON - O/OFF - II/ON

UL/NEMA type	IEC type	Color	Length in/mm	Marking	Defeatable	Padlockable	Weight (lbs)	Shaft size (mm)	Catalog number	List price
1, 3R, 12	IP65	Black Red/Yel	2.6/65	O/I & Off/On	Yes	Yes	0.29	5	OHB65J5E011 OHY65J5E011	\$ 90
1, 3R, 4, 4X, 12	IP66	Black Red/Yel	2.6/65	O/I & Off/On	Yes	Yes	0.29	5	OHB65L5E011 OHY65L5E011	130

Shafts for pistol handles —5mm, for use with transfer switches

Shaft length (inches/mm)	Mounting depth ^② (inches)			Weight (lbs)	Shaft size (mm)	Catalog number	List price
	OT16E3 OT25E3 OT32E3	OT45E3 OT63E3	OT30E3 OT60E3 OT100E3				
5.9/160	7.2	7.4	7.5	0.07	5	OXF5X150	\$ 14
6.7/170	8.0	8.2	8.3	0.08		OXF5X170	16
10.4/265	11.7	11.9	12.0	0.12		OXF5X265	18
15.8/400	17.0	17.2	17.3	0.18		OXF5X400	30
19.7/500	21.0	21.2	21.3	0.23		OXF5X500	42

① A snap on power pole may be added to build a 4 pole transfer switch; please reference accessories and auxiliary contact information on page 17.12.

② Mounting depth is the distance from the outside of door to the disconnect switch mounting plate. Shaft can be cut to desired length.