



125A Accessories


Disconnect
switches
Non-fusible



OBEA-10 OBEA-01




OEZNP1




OAZX1 OA2G11



OTP_160EP



OETL-ZW16



OETL-ZX167
OETL-ZX95

Auxiliary contacts, top mounted

- Accepts four contacts maximum, mounting base always required

Description	For use with:	Weight (lbs)	AC thermal amp rating	AC rated voltage	Catalog number	List price
1 N.O. 1 N.C.	OEZNP1 OT160	0.07	10 10	600 600	OBEA-10 OBEA-01	\$ 28 28
1 N.O. gold plated ^① 1 N.C. gold plated ^①	OEZNP1 OT160	0.07	10 10	600 600	OBEA-10AU OBEA-01AU	56 56
Mounting base – required for OBEA_	OBEA_	0.06	—	—	OEZNP1	20

Auxiliary contacts, side mounted

- Accepts four contacts maximum

Description	For use on:	Weight (lbs)	AC thermal amp rating	AC rated voltage	Catalog number	List price
1 N.O. & 1 N.C.	OT160	0.07	10	600	OA2G11	\$ 40
Mounting base – required for OA2G11	OT160	0.06	—	—	OAZX1	20

Max. two contacts on each side of switch. One mounting base required for each side of switch

Numbering stickers ^②

Description	For use on:	Package qty.	Catalog number	List price
1 Pkg. of blank labels for OBEA-10, 1 N.O.	OT160	10	OBEA-ZX10	\$ 32
1 Pkg. of blank labels for OBEA-01, 1 N.C.	OT160	10	OBEA-ZX01	32

Power pole — for use with base or door mounted switch

- Only one power pole per switch
- Mounts on left or right side of switch

Description	For use on:	Weight (lbs)	AC thermal amp rating	AC rated voltage	Catalog number	List price
Fourth pole	OT160	0.66	125	600	OTPS160EP	\$ 100

Terminal poles — for use with base or door mounted switch

- Switch accepts one terminal pole per side
- Mounts on left or right side of switch

Description	For use on:	Weight (lbs)	AC thermal amp rating	AC rated voltage	Catalog number	List price
Detachable neutral mounts on side of switch or DIN rail	OT160	0.66	125	600	OTPN160EP	\$ 100
Ground terminal	OT160	0.66	125	600	OTPE160EP	100

Locking accessories

Description	For use on:	Weight (lbs)	Catalog number	List price
Cam attachment for Kirk Key, Castell, Lowe & Fletcher and Ronis interlock. For adapting to the interlock system The interlock is not included.	5, 6 & 8mm shafts	0.29	OETL-ZW16	\$ 190

Handle support bracket

Description	For use on:	Weight (lbs)	Catalog number	List price
Allows pistol handle to be directly mounted to switch behind the door	OT160	0.33	OHZX5	\$ 24

Shaft extension couplers

Description	For use on:	Weight (lbs)	Catalog number	List price
Joins two shafts together for applications where extended length is required	for 6mm shafts for 12mm shafts	0.26 0.26	OESA-ZX167 OETL-ZX95	\$ 56 100

^① Type _AU for low energy applications. The contacts are gold-plated. AC & DC ratings — Maximum: A600 & P600. Minimum: 12V, 1mA;

^② Required if several contact blocks are used in the same installation.