


200A

Disconnect
switches
Non-fusible

For a complete assembly,
please select one of each:

- 1 switch
- 1 handle
- 1 shaft
- 1 terminal lug kit



OETL-NF200ASW




OHB__J8



OHY__J8



OXP8X__



OXP8X340-45

175 – 200 Amp switches, 600V

UL general purpose amp rating	IEC AC21 Amp rating	Maximum horsepower rating					Catalog number	List price
		Three phase						
		200V	208V	240V	480V	600V		
2 pole								
200	250	—	—	—	—	—	2 pole OETL-NF200A2SW \$ 560	
3 pole								
200	250	60	60	75	150	200	3 pole OETL-NF200ASW 620	
4 pole								
200	250	60	60	75	150	200	4 pole OETL-NF200A4SW 780	

Pistol handles — for use with shafts $\square .31 \times .31$ " ($\square 8 \times 8$ mm)

UL/NEMA type	IEC type	Color	Length mm	Marking	Defeat-able	Padlock-able	Weight (lbs)	Catalog number	List price
1,3R,12	IP65	Black	2.6/65	O/I & Off/On	Yes	Yes	0.29	OHB65J8	\$ 80
1,3R,12	IP65	Red/Yel	2.6/65	O/I & Off/On	Yes	Yes	0.29	OHY65J8	80
1,3R,12	IP65	Black	3.1/80	O/I & Off/On	Yes	Yes	0.30	OHB80J8	80
1,3R,12	IP65	Red/Yel	3.1/80	O/I & Off/On	Yes	Yes	0.30	OHY80J8	80
1,3R,4,4X,12	IP66	Black	3.1/80	O/I & Off/On	Yes	Yes	0.30	OHB80L8	120
1,3R,4,4X,12	IP66	Red/Yel	3.1/80	O/I & Off/On	Yes	Yes	0.30	OHY80L8	120

Shafts — for use with pistol handles $\square .31 \times .31$ " ($\square 8 \times 8$ mm)

Shaft length inches/mm	Mounting depth ^① in inches OETL-NF175 – OETL-NF200	Weight (lbs)	Catalog number	List price
5.5/140	4.7 – 8.7	0.15	OXP8X140	\$ 16
9.5/240	8.7 – 12.6	0.26	OXP8X240	24
13.4/340	12.6 – 16.6	0.36	OXP8X340	40
19.5/500	18.9 – 22.9	0.54	OXP8X500	48

Twisted shafts — Rotates handle 45° $\square .31 \times .31$ " ($\square 8 \times 8$ mm)

Shaft length inches/mm	Mounting depth ^① in inches OETL-NF175 – OETL-NF200	Weight (lbs)	Catalog number	List price
13.4/340	12.6 – 16.6	0.36	OXP8X340-45	\$ 44

① Mounting depth is the distance from the outside of the door to the disconnect switch mounting plate. Shaft can be cut to desired length.