

1200A – 3150A

Disconnect
switches
Non-fusible

For a complete assembly please select one of each:

- 1 switch
- 1 handle
- 1 shaft
- 1 terminal lug kit



OETL-NF1200ASW



OXP12X280



OHB175J12



OZXA-28



OETL-NF1600SW
OETL-NF2000SW
OETL-NF3150SW



OHB_J12



OHY_J12



YASDA-8



OXP12X_

1200 – 3150 Amp switches, 600V

UL general purpose amp rating	IEC AC21 amp rating	Maximum horsepower rating	Catalog number	List price	
2 pole					
1200	1600	The US National Electric Code does not specify HP ratings for switches this large. Please select a switch based on 115% of application FLA. For example: a motor with an FLA of 800A would require a 1200A switch: 800A x 115% = 920A, the closest higher rated switch is 1200A.	2 pole OETL-NF12002SW	\$ 6200	
1600	2500		OETL-NF16002SW	14,800	
2000	2500		OETL-NF20002SW	15,500	
—	3150		OETL-NF31502SW	17,000	
3 pole					
1200	1600		OETL-NF1200SW	6800	
1600	2500		OETL-NF1600SW	16,400	
2000	2500		OETL-NF2000SW	17,200	
—	3150		OETL-NF3150SW	18,900	
4 pole					
—	1600		OETL-NF12004SW	8600	
—	2500		OETL-NF16004SW	20,500	
—	2500	OETL-NF20004SW	21,500		
—	3150	OETL-NF31504SW	23,600		

Pistol handles — for use with shaft □ .47 x .47" (□ 12 x 12mm)

UL/NEMA type	IEC type	Color	Length mm	Marking	Defeat-able	Padlock-able	Weight (lbs)	Catalog number	List price
For use with OETL-NF1200									
1,3R,12	IP65	Black	5.7/145	O/I & Off/On	Yes	Yes	0.39	OHB145J12	\$ 90
1,3R,12	IP65	Red/Yel	5.7/145	O/I & Off/On	Yes	Yes	0.39	OHY145J12	90
1,3R,12	IP65	Black	6.9/175	O/I & Off/On	Yes	Yes	0.41	OHB175J12	100
1,3R,12	IP65	Red/Yel	6.9/175	O/I & Off/On	Yes	Yes	0.41	OHY175J12	100
1,3R,4,4X,12	IP66	Black	5.7/145	O/I & Off/On	Yes	Yes	0.39	OHB145L12	130
1,3R,4,4X,12	IP66	Red/Yel	5.7/145	O/I & Off/On	Yes	Yes	0.39	OHY145L12	130
1,3R,4,4X,12	IP66	Black	6.9/175	O/I & Off/On	Yes	Yes	0.41	OHB175L12	140
1,3R,4,4X,12	IP65	Red/Yel	6.9/175	O/I & Off/On	Yes	Yes	0.41	OHY175L12	140
1,3R,4,4X,12	IP65	Metal	8.7/220	Off/On	—	Yes	1.50	YASDA-8	190
For use with OETL-NF1600 – OETL-NF3150									
1,3R,4,4X,12	IP65	Metal	8.7/220	Off/On	—	Yes	1.50	YASDA-8	190

Shafts — for use with pistol handles □ .47 x .47" (□ 12 x 12 mm)

Shaft length inches/mm	Mounting depth [Ⓢ] in inches	Weight (lbs)	Catalog number	List price
For use with OETL-NF1200				
11.0/280	11.6 – 15.3	0.77	OXP12X280	\$ 36
12.8/325	13.7 – 17.1	0.90	OXP12X325	40
15.6/397	16.2 – 19.9	1.10	OXP12X395	44
18.3/465	18.9 – 22.6	1.32	OXP12X465	48
21.1/535	21.7 – 25.4	1.54	OXP12X535	52
For use with OETL-NF1600 – OETL-NF3150				
12.8/325	13.7 – 17.1	0.90	OXP12X325	40
15.6/397	16.2 – 19.9	1.10	OXP12X395	44
18.3/465	18.9 – 22.6	1.32	OXP12X465	48
21.1/535	21.7 – 25.4	1.54	OXP12X535	52

Ⓢ Mounting depth is the distance from the outside of the door to the disconnect switch mounting plate. Shaft can be cut to desired length.