

Disconnect
switches
Non-fusible

Other configurations

Flange operated 30A – 200A

For a complete assembly,
please select one of each:

- 1 switch
- 1 handle
- 1 shaft
- 1 terminal lug kit



OETL-NF200A-F + DSFHS-12 + DSFHN-HS12 + OZXA-25

Flange operated switches – 3 pole

UL general purpose amp rating	IEC AC21 amp rating	Maximum horsepower rating					Weight (lbs)	Catalog number	List price
		Three phase							
		200V	208V	240V	480V	600V			
30	40	10	10	10	20	30	OT30E3-F	\$ 500	
60	63	20	20	20	40	40	OT60E3-F	590	
100	115	25	25	25	50	40	OT100E3-F	690	
200	250	60	60	75	150	200	OETL-NF200A-F	890	

Handles

UL/NEMA type	Color	Length inches/mm	Marking	Defeat-able	Padlock-able	Weight (lbs)	Catalog number	List price
1, 3R, 12	Metal	6.9/175	O/I & OFF/ON	Yes	Yes	3.52	DSFHN-HS12	\$ 156
4, 4X	Metal	6.9/175	O/I & OFF/ON	Yes	Yes	3.52	DSFHN-HS4	240

Shafts

For use on	Shaft length (inches)	Maximum enclosure depth (inches)	Weight (lbs)	Catalog number	List price
OT30, 60, 100E3-F	—	16.00	.20	OTFS-16	\$ 25
	—	24.0	0.25	OTFS-24	30
OETL-NF200A-F	12	16.0	0.39	DSFHS-12	28
	17	21.0	0.55	DSFHS-17	40
	22.5	27.0	0.73	DSFHS-22	52

Terminal lug kits

For use on:	Wire size	Kit weight (lbs)	Wire type	Terminal lugs per kit	Catalog number	List price
OT30E3-F OT60E3-F OT100E3-F	#14 – #4 #14 – #4 #14 – 2/0	—	Cu	—	Standard	—
OETL-NF200A-F	#6 – 300 kcmil	0.93	Cu/Al	6	OZXA-25	\$ 80
	#6-300 kcmil	0.47	Cu/Al	3	OZXA-25/P	40
	(6) #14-6	0.55	Cu/Al	3	OZXA-175	180

Door hardware kits – NEMA 12

Description	Weight (lbs)	Catalog number	List price
Safety door latch, 2 point, doors less than 40" high	2.0	KDH2R	\$ 200
Safety door latch, 3 point, doors greater than 40" high	2.5	KDH3R	225

UL Listed
CSA Approved
IEC Rated
CE Marked