

30A, Base & DIN rail mounted UL fuse Class J,CC

Disconnect
switches
Fusible

For a complete assembly,
please select one of each:

- 1 switch
- 1 handle
- 1 shaft



OS30AJ12



OXS5X180



OHB2AJ1




OS30A__12



OHB2__



OHY2__



OXS5X__


30 Amp switches, 600V

UL general purpose amp rating	UL Fuse type 600V	Maximum horsepower rating					Terminal lugs		Catalog number	List price
		Three phase					Wire size	Wire type		
		200V	208V	240V	480V	600V				
3 pole										
30	J	5	7.5	7.5	15	20	#18 – 8	Cu	3 pole OS30AJ12 OS30ACC12	\$ 280
30 ^⓪	CC	5	7.5	7.5	15	20	#18 – 8	Cu		
4 pole										
30	J	5	7.5	7.5	15	20	#18 – 8	Cu	4 Pole OS30AJ22F OS30ACC22F	350
30 ^⓪	CC	5	7.5	7.5	15	20	#18 – 8	Cu		

Selector handles — for use with shafts \square .20 x .20" (\square 5 x 5 mm)

UL/NEMA type	IEC type	Color	Defeat- able	Padlock- able	Weight (lbs.)	Catalog number	List price
All marked both O/I & Off/On							
1,3R,12	IP65	Black	—	Yes	0.16	OHB2AJ1	\$ 28
1,3R,12	IP65	Red/Yel	—	Yes	0.16	OHY2AJ1	28
1,3R,12	IP65	Blk	Yes	Yes	0.16	OHB2AJ	30
1,3R,12	IP65	Red/Yel	Yes	Yes	0.16	OHY2AJ	30

Shafts — for use with OH_2_ selector handles \square .20 x .20" (\square 5 x 5 mm)

Shaft length (inches/mm)	 Mounting depth ^⓪ (in inches)	Weight (lbs.)	Catalog number	List price
3.3/85	5.5 – 5.7	0.04	OXS5X85	\$ 4
4.1/105	5.5 – 6.5	0.04	OXS5X105	4
4.7/120	5.5 – 7.1	0.05	OXS5X120	4
5.1/130	5.5 – 7.5	0.05	OXS5X130	6
7.1/180	6.3 – 9.4	0.08	OXS5X180	6
9.8/250	9.1 – 12.2	0.10	OXS5X250	12
13.0/330	12.2 – 15.4	0.14	OXS5X330	20

^⓪ Rejection style fuses only.