

Disconnect
switches
Fusible

30A, Base & DIN rail mounted Handles & shafts

For a complete assembly,
please select one of each:

- 1 switch
- 1 handle
- 1 shaft



OS30AJ12



OXP5X170




OHB65J5




OHB_J5



OHY_J5




OXP5X_




Test

OHB5



OHB5 Mounted




OHB5 Mounted depth

Pistol handles — for use with shafts $\square .20 \times .20"$ ($\square 5 \times 5 \text{ mm}$)

UL/NEMA type	IEC type	Color	Marking	Length inches/mm	Defeat-able	Padlock-able	Weight (lbs.)	Catalog number	List price
1,3R,12	IP65	Black	O/I & Off/On	1.8/45	Yes	Yes	0.28	OHB45J5	\$ 70
1,3R,12	IP65	R/Y	O/I & Off/On	1.8/45	Yes	Yes	0.28	OHY45J5	70
1,3R,12	IP65	Black	O/I & Off/On	2.6/65	Yes	Yes	0.29	OHB65J5	80
1,3R,12	IP65	R/Y	O/I & Off/On	2.6/65	Yes	Yes	0.29	OHY65J5	80
1,3R,4,4X,12	IP65	Black	O/I & Off/On	2.6/65	Yes	Yes	0.29	OHB65L5	120
1,3R,4,4X,12	IP65	R/Y	O/I & Off/On	2.6/65	Yes	Yes	0.29	OHY65L5	120
1,3R,12	IP65	Black	Off/On/Test	2.6/65	Yes	Yes	0.29	OHB65J5T ①	100
1,3R,12	IP65	R/Y	Off/On/Test	2.6/65	Yes	Yes	0.29	OHY65J5T ①	100

Shafts — for use with pistol handles $\square .20 \times .20"$ ($\square 5 \times 5 \text{ mm}$)

Shaft length (inches/mm)		Mounting depth (in inches)	Weight (lbs.)	Catalog number	List price
5.9/150		4.9 – 8.9	0.07	OXP5X150	\$ 14
6.7/170		5.9 – 9.7	0.08	OXP5X170	16
10.4/265		9.5 – 13.4	0.12	OXP5X265	18
15.8/400		15.0 – 18.7	0.18	OXP5X400	30
19.7/500		20.5 – 22.6	0.23	OXP5X500	42

Direct mount handle — mounts directly to switch, no shaft necessary

UL/NEMA type	Color	Marking	Length mm	Padlockable	Weight (lbs.)	Catalog number	List price
1	Blk	O/I/Test	50	Yes	0.10	OHB5	\$ 60

① The OS30_ switch has a TEST position, accessed by rotating the mechanism 45° counterclockwise from the OFF position. In the TEST position, optional auxiliary contacts, OA4B1C, are actuated but the main switch contacts are not.