

Individual capacitors with fuses and blown fuse indicators, 3 phase 480 Volt, 60 Hz



480 Volt, 60 Hz – 3 phase

Enclosure size	kvar rating	Rated current per phase (amps)	Fuse amps/type	Approx. shipping weight (lbs.)	Enclosure type					
					Indoor – NEMA 1		Outdoor – NEMA 3R		Indoor – NEMA 12	
					Catalog number	List price	Catalog number	List price	Catalog number	List price
43	1.5	1.8	5/CC	8	C44G1.5-3FI	\$ 211	C44R1.5-3FI	\$ 215	C44D1.5-3FI	\$ 215
	2	2.4	6/CC	8	C44G2-3FI	204	C44R2-3FI	222	C44D2-3FI	222
	2.5	3.0	8/CC	8	C44G2.5-3FI	214	C44R2.5-3FI	225	C44D2.5-3FI	225
	3	3.6	10/CC	8	C44G3-3FI	217	C44R3-3FI	228	C44D3-3FI	228
	4	4.8	12/CC	8	C44G4-3FI	220	C44R4-3FI	231	C44D4-3FI	231
	5	6.0	15/CC	8	C44G5-3FI	222	C44R5-3FI	233	C44D5-3FI	233
	6	7.2	20/CC	8	C44G6-3FI	231	C44R6-3FI	242	C44D6-3FI	242
	7.5	9.0	25/CC	8	C44G7.5-3FI	257	C44R7.5-3FI	268	C44D7.5-3FI	268
	8	9.6	25/CC	8	C44G8-3FI	273	C44R8-3FI	284	C44D8-3FI	284
	9	10.8	30/CC	8	C44G9-3FI	284	C44R9-3FI	295	C44D9-3FI	295
	10	12.0	30/CC	8	C44G10-3FI	295	C44R10-3FI	306	C44D10-3FI	306
	12	14.4	45/T	13	C44G12-3FI	300	C44R12-3FI	311	C44D12-3FI	311
	12.5	15.0	45/T	13	C44G12.5-3FI	305	C44R12.5-3FI	316	C44D12.5-3FI	316
	13	15.6	50/T	13	C44G13-3FI	311	C44R13-3FI	322	C44D13-3FI	322
	13.5	16.2	50/T	13	C44G13.5-3FI	313	C44R13.5-3FI	324	C44D13.5-3FI	324
	14	16.8	50/T	8	C44G14-3FI	316	C44R14-3FI	327	C44D14-3FI	327
15	18.0	60/T	8	C44G15-3FI	327	C44R15-3FI	338	C44D15-3FI	338	
16	19.2	60/T	13	C44G16-3FI	332	C44R16-3FI	343	C44D16-3FI	343	
53	17	20.4	50/KGJ	14	C45G17-3FI	343	C45R17-3FI	354	C45D17-3FI	354
	17.5	21.0	50/KGJ	14	C45G17.5-3FI	354	C45R17.5-3FI	365	C45D17.5-3FI	365
	18	21.7	50/KGJ	14	C45G18-3FI	364	C45R18-3FI	375	C45D18-3FI	375
	19	22.8	50/KGJ	14	C45G19-3FI	375	C45R19-3FI	386	C45D19-3FI	386
	20	24.1	50/KGJ	14	C45G20-3FI	386	C45R20-3FI	397	C45D20-3FI	397
	21	25.3	60/KGJ	14	C45G21-3FI	391	C45R21-3FI	402	C45D21-3FI	402
	22	26.5	60/KGJ	14	C45G22-3FI	396	C45R22-3FI	407	C45D22-3FI	407
	22.5	27.1	60/KGJ	14	C45G22.5-3FI	407	C45R22.5-3FI	418	C45D22.5-3FI	418
	24	28.9	60/KGJ	14	C45G24-3FI	418	C45R24-3FI	429	C45D24-3FI	429
	25	30.1	75/KGJ	14	C45G25-3FI	428	C45R25-3FI	439	C45D25-3FI	439
	27	32.5	75/KGJ	14	C45G27-3FI	450	C45R27-3FI	461	C45D27-3FI	461
	30	36.1	80/KGJ	14	C45G30-3FI	482	C45R30-3FI	493	C45D30-3FI	493
	32.5	39.1	100/KGJ	14	C45G32.5-3FI	509	C45R32.5-3FI	520	C45D32.5-3FI	520
	35	42.1	100/KGJ	23	C45G35-3FI	535	C45R35-3FI	546	C45D35-3FI	546
	37.5	45.1	100/KGJ	23	C45G37.5-3FI	546	C45R37.5-3FI	557	C45D37.5-3FI	557
	40	48.1	125/KGJ	23	C45G40-3FI	557	C45R40-3FI	568	C45D40-3FI	568
42.5	51.1	125/KGJ	23	C45G42.5-3FI	589	C45R42.5-3FI	600	C45D42.5-3FI	600	
45	54.1	125/KGJ	25	C45G45-3FI	621	C45R45-3FI	632	C45D45-3FI	632	
47.5	57.1	125/KGJ	25	C45G47.5-3FI	642	C45R47.5-3FI	653	C45D47.5-3FI	653	
50	60.1	150/KGJ	25	C45G50-3FI	664	C45R50-3FI	675	C45D50-3FI	675	
63	52.5	63.1	150/KGJ	37	C46G52.5-3FI	685	C46R52.5-3FI	696	C46D52.5-3FI	696
	55	66.2	150/KGJ	37	C46G55-3FI	707	C46R55-3FI	718	C46D55-3FI	718
	57.5	69.2	150/KGJ	37	C46G57.5-3FI	728	C46R57.5-3FI	739	C46D57.5-3FI	739
	60	72.2	175/KGJ	37	C46G60-3FI	739	C46R60-3FI	750	C46D60-3FI	750
	62.5	75.2	175/KGJ	37	C46G62.5-3FI	766	C46R62.5-3FI	777	C46D62.5-3FI	777
	65	78.2	175/KGJ	37	C46G65-3FI	771	C46R65-3FI	782	C46D65-3FI	782
	70	84.2	200/KGJ	39	C46G70-3FI	792	C46R70-3FI	803	C46D70-3FI	803
	75	90.2	200/KGJ	41	C46G75-3FI	814	C46R75-3FI	825	C46D75-3FI	825
77.5	93.2	200/KGJ	41	C46G77.5-3FI	830	C46R77.5-3FI	841	C46D77.5-3FI	841	
83	80	96.2	225/KGJ	56	C48G80-3FI	856	C48R80-3FI	867	C48D80-3FI	867
	85	102.2	225/KGJ	56	C48G85-3FI	910	C48R85-3FI	921	C48D85-3FI	921
	87.5	105.2	225/KGJ	56	C48G87.5-3FI	937	C48R87.5-3FI	948	C48D87.5-3FI	948
	90	108.3	225/KGJ	56	C48G90-3FI	963	C48R90-3FI	974	C48D90-3FI	974
	95	114.3	250/KGJ	56	C48G95-3FI	1001	C48R95-3FI	1012	C48D95-3FI	1012
	100	120.3	250/KGJ	56	C48G100-3FI	1033	C48R100-3FI	1044	C48D100-3FI	1044
	105	126.3	250/KGJ	59	C48G105-3FI	1280	C48R105-3FI	1291	C48D105-3FI	1291
	110	132.3	250/KGJ	61	C48G110-3FI	1310	C48R110-3FI	1321	C48D110-3FI	1321
	115	138.3	250/KGJ	76	C48G115-3FI	1350	C48R115-3FI	1361	C48D115-3FI	1361
	120	144.3	300/KGJ	76	C48G120-3FI	1390	C48R120-3FI	1401	C48D120-3FI	1401

NOTE: ABB's patented IPE design eliminates the need for additional overcurrent protection when capacitors are electrically connected on the load side of a motor starter circuit breaker or fusible disconnect switch.

Availability to be announced.
Please consult ABB