

## Individual capacitors

### Type CLMD-13

### 208, 240, 480 & 600 Volt, 60 Hz



The CLMD-13 capacitor is ideally suited for use in motor control centers, control panels and other indoor applications. Standard features include:

- Indoor, steel enclosure
- Easy electrical connection by means of a terminal block mounted on top of the capacitor enclosure (#4 — #18GA)
- Convenient ground lug mounted on top of the capacitor enclosure
- Mounting feet for easy installation
- Lightweight, small dimensions, totally dry construction
- Options and accessories include remote state indication

#### 208 Volt, 60 Hz, 3 phase

Enclosure size	kvar rating	Rated current per phase (amps)	Approx. shipping weight (lbs)	Enclosure type	
				Indoor — NEMA 1	
				Catalog number	List price
13	0.8	2.2	6	C11G0.8	\$ 124
	1.1	3.1	6	C11G1.1	129
	2	5.6	6	C11G2	150
	2.5	6.9	6	C11G2.5	161
	3	8.3	6	C11G3	177
	4	11.1	6	C11G4	198
	5	13.9	6	C11G5	241
	7.5	20.8	6	C11G7.5	273

#### 600 Volt, 60 Hz, 3 phase

Enclosure size	kvar rating	Rated current per phase (amps)	Approx. shipping weight (lbs)	Enclosure type	
				Indoor — NEMA 1	
				Catalog number	List price
13	2	1.9	6	C61G2	\$ 145
	3	2.9	6	C61G3	150
	4	3.8	6	C61G4	156
	5	4.8	6	C61G5	166
	7.5	7.2	6	C61G7.5	177
	10	9.6	6	C61G10	193
	15	14.4	6	C61G15	220

#### 240 Volt, 60 Hz, 3 phase

Enclosure size	kvar rating	Rated current per phase (amps)	Approx. shipping weight (lbs)	Enclosure type	
				Indoor — NEMA 1	
				Catalog number	List price
13	1	2.4	6	C21G1	\$ 118
	1.5	3.6	6	C21G1.5	124
	2	4.8	6	C21G2	129
	2.5	6.0	6	C21G2.5	145
	3.5	8.4	6	C21G3.5	161
	5	12.0	6	C21G5	172
	7.5	18.0	6	C21G7.5	220
	10	24.1	6	C21G10	257

#### Options

Type	Catalog number suffix ①	List price adder
Remote state indication two LEDs	-2L	\$ 65

**NOTE: ABB's patented IPE design eliminates the need for additional overcurrent protection when capacitors are electrically connected on the load side of a motor starter circuit breaker or fusible disconnect switch.**

#### 480 Volt, 60 Hz, 3 phase

Enclosure size	kvar rating	Rated current per phase (amps)	Approx. shipping weight (lbs)	Enclosure type	
				Indoor — NEMA 1	
				Catalog number	List price
13	0.9	1.1	6	C41G0.9	\$ 118
	1.5	1.8	6	C41G1.5	129
	2	2.4	6	C41G2	134
	2.5	3.0	6	C41G2.5	140
	3.5	4.2	6	C41G3.5	156
	4	4.8	6	C41G4	158
	5	6.0	6	C41G5	166
	6	7.2	6	C41G6	172
	7.5	9.0	6	C41G7.5	177
	8	9.6	6	C41G8	182
	9	10.8	6	C41G9	188
	10	12.0	6	C41G10	193
	14	16.8	6	C41G14	204
	15	18.0	6	C41G15	214
	17	20.4	6	C41G17	225

Availability to be announced.  
Please consult ABB

① Add suffix to end of catalog number.