

Selection guide TA25DU – TA80DU

2



TA25DU



TA42DU



TA75DU



TA80DU

Types

Main characteristics

Construction	3 pole with ambient temperature variation compensation. Protection against single phase operation. Built in auxiliary contacts: 1N.O. + 1N.C.				
Resetting	Convertible: Manual to Automatic				
Setting ranges	Number	18	3	6	4
	from	0.1 – 0.16A	18 – 25A	18 – 25A	29 – 42A
	to	24 – 32A	29 – 42A	60 – 80A	60 – 80A
Mounted with contactors	No kit is required for mounting thermal O/L relays below contactors				
Mounting kit	No kit is required for mounting thermal O/L relays below contactors				
Types of contactors for combined mounting	A/AE/AL9 A/AE/AL12 A/AE/AL16				
	A/AE/AL26 A/AE/AL30 A/AE/AL40	A/AE30 A/AE40			
			A/AE/AF50 A/AE/AF63 A/AE/AF75		
				A/AE/AF95 A/AE/AF110	
Mounted separately (i.e. separate from contactor)				-	
Separate mounting kit	DB25		DB80	-	
Accessories					
Tripping coil	DS25-A				
Resetting coil	DR25-A				
Terminal shroud	Terminals protected against direct contact (without the addition of terminal shrouds)				
Function markers	BA5-50				