

Type TA, Class 10 for Contactors A9 – A/AF300

2




TA25DU



TA42DU



TA75DU



TA80DU



TA110DU

For contactor	Setting range A	Suffix Code	Catalog number	List price
A/AE/AL9 – A/AE/AL40	0.1 – 0.16	A	TA25DU0.16	\$ 63
	0.16 – 0.25	B	TA25DU0.25	
	0.25 – 0.4	C	TA25DU0.4	
	0.4 – 0.63	D	TA25DU0.63	
	0.63 – 1.0	E	TA25DU1.0	
	1.0 – 1.4	F	TA25DU1.4	
	1.3 – 1.8	G	TA25DU1.8	
	1.7 – 2.4	H	TA25DU2.4	
	2.2 – 3.1	J	TA25DU3.1	
	2.8 – 4.0	K	TA25DU4.0	
	3.5 – 5.0	L	TA25DU5.0	
	4.5 – 6.5	M	TA25DU6.5	
	6.0 – 8.5	N	TA25DU8.5	
	7.5 – 11	P	TA25DU11	
10 – 14	Q	TA25DU14		
13 – 19	R	TA25DU19		
18 – 25	S	TA25DU25		
24 – 32	T	TA25DU32		
A/AE30 – A/AE40	18 – 25	A	TA42DU25	78
	22 – 32	B	TA42DU32	
	29 – 42	C	TA42DU42	
A/AE/AF50 – A/AE/AF75	18 – 25	A	TA75DU25	102
	22 – 32	B	TA75DU32	
	29 – 42	C	TA75DU42	
	36 – 52	D	TA75DU52	
	45 – 63	E	TA75DU63	
	60 – 80	F	TA75DU80	
A/AE/AF95 – A/AE/AF110	29 – 42	C	TA80DU42	135
	36 – 52	D	TA80DU52	
	45 – 63	E	TA80DU63	
	60 – 80	F	TA80DU80	
	65 – 90	A	TA110DU90	165
	80 – 110	B	TA110DU110	
A/AF145 – A/AF185	65 – 90	A	TA200DU90	165
	80 – 110	B	TA200DU110	
	100 – 135	C	TA200DU135	225
	110 – 150	D	TA200DU150	
	130 – 175	E	TA200DU175	
	150 – 200	F	TA200DU200	
A/AF210 – A/AF300	130 – 185	A	TA450DU185 ①	488
	165 – 235	B	TA450DU235	
	220 – 310	C	TA450DU310	
AF400 – AF750	See electronic overloads, pages 2.21			

① TA450 overloads require mounting kits for installation.