


## Approximate dimensions Circuit breaker, across the line Reversing, non-fused w/CCT

Combination  
starters

3



### Circuit breaker, across the line

Starter size	Enclosure type	A	B	C
A9 – A40 (S3)	1	14	12	8
	3R	14	12	8
	4	16	12	8
	4X Stainless	16	12	8
	4X Plastic	14	12	7
	12	14	12	8
	7 ③	14	10	6
A50 – A75 (S3)	1	14	12	8
	3R	14	12	8
	4	16	12	8
	4X Stainless	16	12	8
	4X Plastic	14	12	7
	12	14	12	8
	7 ③	18	12	6
A95 – A110 (S3)	1	20	16	8
	3R	20	16	8
	4	20	16	8
	4X Stainless	20	16	8
	4X Plastic	20	16	8
	12	20	16	8
	7 ③	24	16	6
A145 – A185 (S3, S4) ①	1	24	20	8
	3R	24	16	8
	4	24	16	8
	4X Stainless	24	16	8
	4X Plastic	30	20	12
	12	24	16	8
	7 ③	24	16	6
A210 – A300 (S4, S5) ①	1	30	24	12
	3R	30	20	10
	4	30	20	10
	4X Stainless	30	24	12
	4X Plastic	30	20	12
	12	30	20	10
	7 ③	30	18	8
A300 (S6) ②	1	36	30	12
	3R	36	30	12
	4	36	30	12
	4X Stainless	36	30	12
	4X Plastic	33	25	12
	12	36	30	12
	7 ③	30	24	8
A400 (S6) ①	1	30	24	12
	3R	30	24	10
	4	30	24	10
	4X Stainless	30	24	12
	4X Plastic	33	25	12
	12	30	24	10
A460 – A580 (S6) ①	1	36	30	12
	3R	36	24	12
	4	36	24	12
	4X Stainless	36	24	12
	4X Plastic	–	–	–
	12	36	24	12
A580 (S7) ②	1	42	30	13
	3R	42	36	12
	4	42	36	12
	4X Stainless	42	36	12
	4X Plastic	–	–	–
	12	42	36	12
A750 (S7) ②	1	48	36	13
	3R	48	36	13
	4	48	36	13
	4X Stainless	48	36	13
	4X Plastic	–	–	–
	12	48	36	13

### Reversing, non-fused w/CCT

Starter size	Enclosure type	A	B	C
A9 – A40	1	14	12	8
	3R	14	12	8
	4	14	12	6
	4X Stainless	14	12	6
	4X Plastic	14	12	7
	12	14	12	8
A50 – A75	1	20	16	8
	3R	20	16	8
	4	20	16	8
	4X Stainless	20	16	8
	4X Plastic	20	16	8
	12	20	16	8
A95 – A110	1	30	24	8
	3R	30	24	8
	4	30	24	8
	4X Stainless	30	24	8
	4X Plastic	30	30	12
	12	30	24	8
A145 – A185	1	30	24	12
	3R	30	24	8
	4	30	24	8
	4X Stainless	30	24	8
	4X Plastic	33	25	12
	12	30	24	8
A210	1	30	24	12
	3R	30	24	10
	4	30	24	10
	4X Stainless	30	24	10
	4X Plastic	33	25	12
	12	30	24	10
A260 – A300	1	36	30	12
	3R	30	30	10
	4	30	30	10
	4X Stainless	36	30	12
	4X Plastic	40	30	12
	12	30	30	10
A400 – A460	1	48	36	13
	3R	48	36	12
	4	48	36	12
	4X Stainless	48	36	12
	4X Plastic	–	–	–
	12	48	36	12
A580 – A750	1	87	36	24
	3R	87	36	24
	4	87	36	24
	4X Stainless	–	–	–
	4X Plastic	–	–	–
	12	87	36	24

① Busbars breaker-starter, bottom entry

② Cable, breaker-starter.

③ Type 7, explosion-proof inside dimensions.