


Approximate dimensions 2 Speed, 1 winding, breaker combination w/CCT

3



2 Speed - 1 Winding, breaker combination w/CCT

Starter size	Enclosure type	A	B	C
A9 – A40	1	14	12	8
	3R	14	12	8
	4	14	12	8
	4X Stainless	16	12	8
	4X Plastic	14	12	7
	12	14	12	8
A50 – A75	1	24	20	8
	3R	24	20	8
	4	24	20	8
	4X Stainless	24	20	8
	4X Plastic	30	20	12
	12	24	20	8
A95 – A110	1	36	30	12
	3R	36	30	12
	4	36	30	12
	4X Stainless	36	30	12
	4X Plastic	40	30	14
	12	36	30	12
A145 (S3) A185 (S3, S4)	1	36	24	8
	3R	36	24	8
	4	36	24	8
	4X Stainless	36	24	8
	4X Plastic	40	30	14
	12	36	24	8
A210 – A300 (S4, S5)	1	36	30	12
	3R	36	30	12
	4	36	30	12
	4X Stainless	36	30	12
	4X Plastic	40	30	14
	12	36	30	12
A300 (S6)	1	42	30	13
	3R	42	36	12
	4	42	36	12
	4X Stainless	42	36	12
	4X Plastic	–	–	–
	12	42	36	12
A400 (S6)	1	48	36	13
	3R	48	36	12
	4	48	36	12
	4X Stainless	48	36	12
	4X Plastic	–	–	–
	12	48	36	12
A460 (S6)	1	48	36	13
	3R	48	36	12
	4	48	36	12
	4X Stainless	48	36	12
	4X Plastic	–	–	–
	12	48	36	12
A580 (S6)	1	–	–	–
	3R	60	36	12
	4	60	36	12
	4X Stainless	60	36	12
	4X Plastic	–	–	–
	12	60	36	12
A580 – A750 (S7)	1	87	36	24
	3R	87	36	24
	4	–	–	–
	4X Stainless	–	–	–
	4X Plastic	–	–	–
	12	87	36	24