

Wye-delta, open transition Three phase

Reduced voltage
starters

3

UL Type 3R (Outdoor Metal)		UL Type 12 (Metal Dusttight)		UL Type 4 (Watertight)		UL Type 4X (Stainless Steel)	
Catalog number	List price	Catalog number	List price	Catalog number	List price	Catalog number	List price
UL rated							
A26SG3-84★◆	\$ 3992	A26SG2-84★◆	\$ 3992	A26SG4-84★◆	\$ 4172	A26SGX-84★◆	\$ 4800
A30SG3-84★◆	4335	A30SG2-84★◆	4335	A30SG4-84★◆	4485	A30SGX-84★◆	5138
A40SG3-84★◆	4425	A40SG2-84★◆	4425	A40SG4-84★◆	4575	A40SGX-84★◆	5400
A50SG3-84★◆	4784	A50SG2-84★◆	4784	A50SG4-84★◆	4874	A50SGX-84★◆	5738
A63SG3-84★◆	5847	A63SG2-84★◆	5847	A63SG4-84★◆	5850	A63SGX-84★◆	6750
A75SG3-84★◆	6674	A75SG2-84★◆	6674	A75SG4-84★◆	7079	A75SGX-84★◆	8438
A95SG3-84★◆	7875	A95SG2-84★◆	7875	A95SG4-84★◆	8205	A95SGX-84★◆	9625
A110SG3-84★◆	10,508	A110SG2-84★◆	10,508	A110SG4-84★◆	10,950	A110SGX-84★◆	13,125
A145SG3-84★◆	12,902	A145SG2-84★◆	12,902	A145SG4-84★◆	13,865	A145SGX-84★◆	16,238
A185SG3-84★◆	14,385	A185SG2-84★◆	14,385	A185SG4-84★◆	15,150	A185SGX-84★◆	18,150
A210SG3-84★◆	18,215	A210SG2-84★◆	18,215	A210SG4-84★◆	19,035	A210SGX-84★◆	21,450
A260SG3-84★◆	22,388	A260SG2-84★◆	22,388	A260SG4-84★◆	25,088	A260SGX-84★◆	27,338
A300SG3-84★◆	30,383	A300SG2-84★◆	30,383	A300SG4-84★◆	31,538	A300SGX-84★◆	35,475
A400SG3-84★◆	41,150	A400SG2-84★◆	41,150	A400SG4-84★◆	42,816	A400SGX-84★◆	46,575
A460SG3-70★◆	46,085	A460SG2-70★◆	46,085	A460SG4-70★◆	49,460	A460SGX-70★◆	51,900
A580SG3-70★◆	54,576	A580SG2-70★◆	54,576	A580SG4-70★◆	57,783	A580SGX-70★◆	61,425
A750SG3-70★◆	60,980	A750SG2-70★◆	60,980	A750SG4-70★◆	64,355	A750SGX-70★◆	70,125

NEMA rated							
A26NSG3-84★◆	\$ 3992	A26NSG2-84★◆	\$ 3992	A26NSG4-84★◆	\$ 4172	A26NSGX-84★◆	\$ 4800
A50NSG3-84★◆	4784	A50NSG2-84★◆	4784	A50NSG4-84★◆	4874	A50NSGX-84★◆	5738
A75NSG3-84★◆	6674	A75NSG2-84★◆	6674	A75NSG4-84★◆	7079	A75NSGX-84★◆	8438
A145NSG3-84★◆	12,902	A145NSG2-84★◆	12,902	A145NSG4-84★◆	13,865	A145NSGX-84★◆	16,238
A260NSG3-84★◆	22,388	A260NSG2-84★◆	22,388	A260NSG4-84★◆	25,088	A260NSGX-84★◆	27,338
A460NSG3-70★◆	46,085	A460NSG2-70★◆	46,085	A460NSG4-70★◆	49,460	A460NSGX-70★◆	51,900
A750NSG3-70★◆	60,980	A750NSG2-70★◆	60,980	A750NSG4-70★◆	64,355	A750NSGX-70★◆	70,125

- ★ Overload Relay suffix code. Select from the overload relay selection chart on page 3.6.
- ◆ Horsepower and line voltage suffix code. Select from page 3.74.

Control transformer option

Contactor size	VA rating	List price adder
A9 – A40	45 ①	\$ 300
A9 – A40	50	360
A50 – A75	75	435
A95 – A110	100	560
A145 – A185	150	720
A210 – A300	250	795
A400 – A460	150	720 ②
A580 – A750	250	795 ②

① No primary fusing provided.
 ② A400 - A750 utilizes the AF wide range coil with a lower coil consumption than A210 - A300.