

Wye-delta – closed transition Three phase

**Reduced voltage
starters**

3

UL Type 3R (Outdoor metal)		Type 12 (Metal dustight)		UL Type 4 (Watertight)		UL Type 4X (Stainless steel)	
Catalog number	List price	Catalog number	List price	Catalog number	List price	Catalog number	List price

UL rated

A26SY3-84★◆	\$ 5621	A26SY2-84★◆	\$ 5621	A26SY4-84★◆	\$ 5801	A26SYX-84★◆	\$ 6450
A30SY3-84★◆	5921	A30SY2-84★◆	5921	A30SY4-84★◆	6101	A30SYX-84★◆	6788
A40SY3-84★◆	6467	A40SY2-84★◆	6467	A40SY4-84★◆	6557	A40SYX-84★◆	7275
A50SY3-84★◆	6665	A50SY2-84★◆	6665	A50SY4-84★◆	6755	A50SYX-84★◆	7650
A63SY3-84★◆	8942	A63SY2-84★◆	8942	A63SY4-84★◆	9347	A63SYX-84★◆	10,163
A75SY3-84★◆	9689	A75SY2-84★◆	9689	A75SY4-84★◆	10,094	A75SYX-84★◆	11,138
A95SY3-84★◆	14,900	A95SY2-84★◆	14,900	A95SY4-84★◆	15,900	A95SYX-84★◆	17,000
A110SY3-84★◆	15,907	A110SY2-84★◆	15,907	A110SY4-84★◆	16,870	A110SYX-84★◆	18,350
A145SY3-84★◆	17,123	A145SY2-84★◆	17,023	A145SY4-84★◆	18,086	A145SYX-84★◆	19,950
A185SY3-84★◆	22,973	A185SY2-84★◆	22,973	A185SY4-84★◆	28,436	A185SYX-84★◆	30,225
A210SY3-84★◆	27,482	A210SY2-84★◆	27,482	A210SY4-84★◆	30,182	A210SYX-84★◆	32,400
A260SY3-84★◆	28,841	A260SY2-84★◆	28,841	A260SY4-84★◆	31,541	A260SYX-84★◆	33,450
A300SY3-84★◆	34,991	A300SY2-84★◆	34,991	A300SY4-84★◆	37,691	A300SYX-84★◆	40,688
A400SY3-70★◆	41,250	A400SY2-70★◆	41,250	A400SY4-70★◆	45,330	A400SYX-70★◆	48,675
A460SY3-70★◆	57,101	A460SY2-70★◆	57,101	A460SY4-70★◆	60,476	A460SYX-70★◆	66,900
A580SY3-70★◆	72,749	A580SY2-70★◆	72,749	A580SY4-70★◆	75,633	A580SYX-70★◆	83,625
A750SY3-70★◆	78,071	A750SY2-70★◆	78,071	A750SY4-70★◆	81,446	A750SYX-70★◆	88,725

NEMA rated

A26NSY3-84★◆	\$ 5621	A26NSY2-84★◆	\$ 5621	A26NSY4-84★◆	\$ 5801	A26NSYX-84★◆	\$ 6450
A50NSY3-84★◆	6665	A50NSY2-84★◆	6665	A50NSY4-84★◆	6755	A50NSYX-84★◆	7650
A75NSY3-84★◆	9689	A75NSY2-84★◆	9689	A75NSY4-84★◆	10,094	A75NSYX-84★◆	11,138
A145NSY3-84★◆	17,123	A145NSY2-84★◆	17,023	A145NSY4-84★◆	18,086	A145NSYX-84★◆	19,950
A260NSY3-84★◆	28,841	A260NSY2-84★◆	28,841	A260NSY4-84★◆	31,541	A260NSYX-84★◆	33,450
A460NSY3-70★◆	57,101	A460NSY2-70★◆	57,101	A460NSY4-70★◆	60,476	A460NSYX-70★◆	66,900
A750NSY3-70★◆	78,071	A580NSY2-70★◆	78,071	A750NSY4-70★◆	81,446	A750NSYX-70★◆	88,725

★ Overload Relay suffix code. Select from the overload relay selection chart on page 3.6.

◆ Horsepower and line voltage suffix code. Select from page 3.74.

Control transformer option

Contactor size	VA rating	List price adder
A9 – A40	45 ①	\$ 300
A9 – A40	50	360
A50 – A75	75	435
A95 – A110	100	560
A145 – A185	150	720
A210 – A300	250	795
A400 – A460	150	720 ②
A580 – A750	250	795 ②

① No primary fusing provided.

② A400 - A750 utilizes the AF wide range coil with a lower coil consumption than A210 - A300.