

Part winding – non-reversing Three phase

**Reduced voltage
starters**

3

UL Type 3R (Outdoor metal)		UL Type 12 (Metal dusttight)		UL Type 4 (Watertight)		UL Type 4X (Stainless steel)	
Catalog number	List price	Catalog number	List price	Catalog number	List price	Catalog number	List price

UL rated

A26SH3-84★◆	\$ 2871	A26SH2-84★◆	\$ 2871	A26SH4-84★◆	\$ 3051	A26SHX-84★◆	\$ 3638
A30SH3-84★◆	3075	A30SH2-84★◆	3075	A30SH4-84★◆	3233	A30SHX-84★◆	3825
A40SH3-84★◆	3543	A40SH2-84★◆	3543	A40SH4-84★◆	3723	A40SHX-84★◆	4313
A50SH3-84★◆	3933	A50SH2-84★◆	3933	A50SH4-84★◆	4023	A50SHX-84★◆	4500
A63SH3-84★◆	4583	A63SH2-84★◆	4583	A63SH4-84★◆	4673	A63SHX-84★◆	5363
A75SH3-84★◆	5310	A75SH2-84★◆	5310	A75SH4-84★◆	5715	A75SHX-84★◆	6540
A95SH3-84★◆	8500	A95SH2-84★◆	8500	A95SH4-84★◆	8700	A95SHX-84★◆	9300
A110SH3-84★◆	8745	A110SH2-84★◆	8745	A110SH4-84★◆	9150	A110SHX-84★◆	9900
A145SH3-84★◆	10,269	A145SH2-84★◆	10,269	A145SH4-84★◆	11,232	A145SHX-84★◆	12,225
A185SH3-84★◆	12,369	A185SH2-84★◆	12,369	A185SH4-84★◆	13,332	A185SHX-84★◆	14,813
A210SH3-84★◆	16,569	A210SH2-84★◆	16,569	A210SH4-84★◆	17,532	A210SHX-84★◆	19,050
A260SH3-84★◆	20,169	A260SH2-84★◆	20,169	A260SH4-84★◆	22,869	A260SHX-84★◆	26,100
A300SH3-84★◆	34,020	A300SH2-84★◆	34,020	A300SH4-84★◆	36,720	A300SHX-84★◆	38,225
A400SH3-70★◆	41,589	A400SH2-70★◆	41,589	A400SH4-70★◆	42,552	A400SHX-70★◆	45,263
A460SH3-70★◆	47,438	A460SH2-70★◆	47,438	A460SH4-70★◆	48,401	A460SHX-70★◆	49,913
A580SH3-70★◆	55,971	A580SH2-70★◆	55,971	A580SH4-70★◆	56,934	A580SHX-70★◆	59,400
A750SH3-70★◆	62,064	A750SH2-70★◆	62,064	A750SH4-70★◆	62,541	A750SHX-70★◆	66,150

NEMA rated

A26NSH3-84★◆	\$ 2871	A26NSH2-84★◆	\$ 2871	A26NSH4-84★◆	\$ 3051	A26NSHX-84★◆	\$ 3638
A50NSH3-84★◆	3933	A50NSH2-84★◆	3933	A50NSH4-84★◆	4023	A50NSHX-84★◆	4500
A75NSH3-84★◆	5310	A75NSH2-84★◆	5310	A75NSH4-84★◆	5715	A75NSHX-84★◆	6540
A145NSH3-84★◆	10,269	A145NSH2-84★◆	10,269	A145NSH4-84★◆	11,232	A145NSHX-84★◆	12,225
A260NSH3-84★◆	20,169	A260NSH2-84★◆	20,169	A260NSH4-84★◆	22,869	A260NSHX-84★◆	26,100
A460NSH3-70★◆	47,438	A460NSH2-70★◆	47,438	A460NSH4-70★◆	48,401	A460NSHX-70★◆	49,913
A750NSH3-70★◆	62,064	A750NSH2-70★◆	62,064	A750NSH4-70★◆	62,541	A750NSHX-70★◆	66,150

- ★ Overload Relay suffix code. Select from the overload relay selection chart on page 3.6.
- ◆ Horsepower and line voltage suffix code. Select from page 3.74.

Control transformer option

Contactor size	VA rating	List price adder
A9 – A40	45 ①	\$ 300
A9 – A40	50	360
A50 – A75	75	435
A95 – A110	100	560
A145 – A185	150	720
A210 – A300	250	795
A400 – A460	150	720 ②
A580 – A750	250	795 ②

① No primary fusing provided.
 ② A400 - A750 utilizes the AF wide range coil with a lower coil consumption than A210 - A300.