

Type MS116



MS116

5

Manual motor protectors

Thermal setting range (Amps)	Single-phase horsepower ratings ①		3-phase horsepower ratings			Catalog number	List price
	120V	240V	240V	480V	600V		
MS116							
0.10 – 0.16	—	—	—	—	—	MS116-0.16	\$ 129
0.16 – 0.25	—	—	—	—	—	MS116-0.25	
0.25 – 0.40	—	—	—	—	—	MS116-0.40	
0.40 – 0.63	—	—	—	—	—	MS116-0.63	
0.63 – 1.0	—	—	—	1/2	1/2	MS116-1.0	148.50
1.0 – 1.6	—	1/10	—	3/4	3/4	MS116-1.6	
1.6 – 2.5	—	1/6	1/2	1	1.5	MS116-2.5	
2.5 – 4.0	1/8	1/3	1	2	3	MS116-4.0	
4.0 – 6.3	1/4	1/2	1.5	3	5	MS116-6.3	
6.3 – 10	1/2	1.5	3	5	7.5	MS116-10	
8.0 – 12	1/2	2	3	7.5	10	MS116-12	172.50
10.0 – 16	1	2	5	10	10	MS116-16	

UL File # E137861

① Single phase motor ratings are based upon wiring all three poles in series.