



## Type PST, Enclosed NEMA 1, 12 In-Line, 5 – 1000 HP

### Connected In-Line

Max. motor current		Maximum horsepower					NEMA1, 480V	NEMA1, 600V	List Price	NEMA12, 480V	NEMA12, 600V	List Price
UL	IEC	208V	240V	380V	480V	600V	Catalog Number	Catalog Number		Catalog Number	Catalog Number	
18	18	5	5	10	10	—	T010L1-48	—	<b>\$ 1655</b>	T010L2-48M	—	<b>\$ 1905</b>
		—	—	—	—	15	—	T015L1-60		—	T015L2-60M	
28	30	7.5	10	15	20	—	T020L1-48	—	<b>1655</b>	T020L2-48M	—	<b>1930</b>
		—	—	—	—	25	—	T025L1-60		—	T025L2-60M	
34	37	10	10	20	25	—	T025L1-48	—	<b>1685</b>	T025L2-48M	—	<b>2085</b>
		—	—	—	—	30	—	T030L1-60		—	T030L2-60M	
42	44	10	15	25	30	—	T030L1-48	—	<b>1715</b>	T030L2-48M	—	<b>2165</b>
		—	—	—	—	40	—	T040L1-60		—	T040L2-60M	
54	50	15	20	30	40	—	T040L1-48	—	<b>2055</b>	T040L2-48M	—	<b>2555</b>
		—	—	—	—	50	—	T050L1-60		—	T050L2-60M	
68	72	20	25	40	50	—	T050L1-48	—	<b>2080</b>	T050L2-48M	—	<b>2630</b>
		—	—	—	—	60	—	T060L1-60		—	T060L2-60M	
80	85	25	30	50	60	—	T060L1-48	—	<b>2705</b>	T060L2-48M	—	<b>3355</b>
		—	—	—	—	75	—	T075L1-60		—	T075L2-60M	
104	105	30	40	60	75	—	T075L1-48	—	<b>2735</b>	T075L2-48M	—	<b>3460</b>
		—	—	—	—	100	—	T100L1-60		—	T100L2-60M	
130	142	40	50	75	100	—	T100L1-48	—	<b>3875</b>	T100L2-48M	—	<b>4775</b>
		—	—	—	—	125	—	T125L1-60		—	T125L2-60M	
156	150	50	60	100	125	—	T125L1-48	—	<b>3920</b>	T125L2-48M	—	<b>5120</b>
		—	—	—	—	150	—	T150L1-60		—	T150L2-60M	
192	210	60	75	125	150	—	T150L1-48	—	<b>4370</b>	T150L2-48M	—	<b>5770</b>
		—	—	—	—	200	—	T200L1-60		—	T200L2-60M	
248	250	75	100	150	200	—	T200L1-48	—	<b>4850</b>	T200L2-48M	—	<b>6550</b>
		—	—	—	—	250	—	T250L1-60		—	T250L2-60M	
302	300	100	100	150	250	—	T250L1-48	—	<b>5080</b>	T250L2-48M	—	<b>7830</b>
		—	—	—	—	300	—	T300L1-60		—	T300L2-60M	
361	370	125	150	200	300	—	T300L1-48M <sup>①</sup>	—	<b>6260</b>	T300L2-48M <sup>①</sup>	—	<b>6910</b>
		—	—	—	—	350	—	T350L1-60M <sup>①</sup>		—	T350L2-60M <sup>①</sup>	
414	400	—	—	250	350	—	T350L1-48M <sup>①</sup>	—	<b>7700</b>	T350L2-48M <sup>①</sup>	—	<b>8550</b>
		—	—	—	—	400	—	T400L1-60M <sup>①</sup>		—	T400L2-60M <sup>①</sup>	
480	470	150	200	300	400	—	T400L1-48M <sup>①</sup>	—	<b>7700</b>	T400L2-48M <sup>①</sup>	—	<b>8550</b>
		—	—	—	—	500	—	T500L1-60M <sup>①</sup>		—	T500L2-60M <sup>①</sup>	
590	570	200	250	350	500	—	T500L1-48M <sup>①</sup>	—	<b>9350</b>	T500L2-48M <sup>①</sup>	—	<b>10,350</b>
		—	—	—	—	600	—	T600L1-60M <sup>①</sup>		—	T600L2-60M <sup>①</sup>	
720	720	250	300	450	600	—	T600L1-48M <sup>①</sup>	—	<b>10,830</b>	T600L2-48M <sup>①</sup>	—	<b>11,830</b>
		—	—	—	—	700	—	T700L1-60M <sup>①</sup>		—	T700L2-60M <sup>①</sup>	
840	840	300	350	500	700	—	T700L1-48M <sup>①</sup>	—	<b>12,900</b>	T700L2-48M <sup>①</sup>	—	<b>14,000</b>
		—	—	—	—	800	—	T800L1-60M <sup>①</sup>		—	T800L2-60M <sup>①</sup>	
960	—	350	400	—	800	—	T800L1-48M <sup>①</sup>	—	<b>21,000</b>	T800L2-48M <sup>①</sup>	—	<b>22,300</b>
		—	—	—	—	900	—	T900L1-60M <sup>①</sup>		—	T900L2-60M <sup>①</sup>	
1062	1050	400	450	600	900	—	T900L1-48M <sup>①</sup>	—	<b>21,000</b>	T900L2-48M <sup>①</sup>	—	<b>22,300</b>
		—	—	—	—	1000	—	T1000L1-60M <sup>①</sup>		—	T1000L2-60M <sup>①</sup>	

① Includes integrated shunt rated (AC1) bypass contactor as standard. For across the line rated (AC3) bypass contactors, see page 6.30.