

Type PST, Enclosed NEMA 1, 12 Inside Delta, 7.5 – 1800 HP



Connected Inside Delta

Max. motor current		Maximum horsepower					NEMA1, 480V	NEMA1, 600V	List Price	NEMA12, 480V	NEMA12, 600V	List Price
UL	IEC	208V	240V	380V	480V	600V	Catalog Number	Catalog Number		Catalog Number	Catalog Number	
28	30	7.5	10	15	20	—	T020D1-48	—	\$ 1655	T020D2-48M	—	\$ 1905
		—	—	—	—	25	—	T025D1-60		—	T025D2-60M	
34	37	10	10	20	25	—	T025D1-48	—	1655	T025D2-48M	—	1905
		—	—	—	—	30	—	T030D1-60		—	T030D2-60M	
42	44	10	15	25	30	—	T030D1-48	—	1655	T030D2-48M	—	1930
		—	—	—	—	40	—	T040D1-60		—	T040D2-60M	
54	50	15	20	30	40	—	T040D1-48	—	1685	T040D2-48M	—	2085
		—	—	—	—	50	—	T050D1-60		—	T050D2-60M	
68	72	20	25	40	50	—	T050D1-48	—	1715	T050D2-48M	—	2165
		—	—	—	—	60	—	T060D1-60		—	T060D2-60M	
80	85	25	30	50	60	—	T060D1-48	—	2055	T060D2-48M	—	2555
		—	—	—	—	75	—	T075D1-60		—	T075D2-60M	
104	105	30	40	60	75	—	T075D1-48	—	2080	T075D2-48M	—	2630
		—	—	—	—	100	—	T100D1-60		—	T100D2-60M	
130	142	40	50	75	100	—	T100D1-48	—	2705	T100D2-48M	—	3355
		—	—	—	—	125	—	T125D1-60		—	T125D2-60M	
156	150	50	60	100	125	—	T125D1-48	—	2735	T125D2-48M	—	3460
		—	—	—	—	150	—	T150D1-60		—	T150D2-60M	
192	210	60	75	125	150	—	T150D1-48	—	3875	T150D2-48M	—	4775
		—	—	—	—	200	—	T200D1-60		—	T200D2-60M	
248	250	75	100	150	200	—	T200D1-48	—	3920	T200D2-48M	—	5120
		—	—	—	—	250	—	T250D1-60		—	T250D2-60M	
302	300	100	100	150	250	—	T250D1-48	—	4370	T250D2-48M	—	5770
		—	—	—	—	300	—	T300D1-60		—	T300D2-60M	
361	370	125	150	200	300	—	T300D1-48	—	4850	T300D2-48M	—	6550
		—	—	—	—	350	—	T350D1-60		—	T350D2-60M	
414	400	—	—	250	350	—	T350D1-48	—	5080	T350D2-48M	—	7830
		—	—	—	—	400	—	T400D1-60		—	T400D2-60M	
480	470	150	200	300	400	—	T400D1-48	—	5080	T400D2-48M	—	7830
		—	—	—	—	500	—	T500D1-60		—	T500D2-60M	
590	570	200	250	350	500	—	T500D1-48M ^①	—	6260	T500D2-48M ^①	—	6910
		—	—	—	—	600	—	T600D1-60M ^①		—	T600D2-60M ^①	
720	720	250	300	450	600	—	T600D1-48M ^①	—	7700	T600D2-48M ^①	—	8550
		—	—	—	—	700	—	T700D1-60M ^①		—	T700D2-60M ^①	
840	840	300	350	500	700	—	T700D1-48M ^①	—	9350	T700D2-48M ^①	—	10,350
		—	—	—	—	800	—	T800D1-60M ^①		—	T800D2-60M ^①	
960	—	350	400	—	800	—	T800D1-48M ^①	—	10,830	T800D2-48M ^①	—	12,130
		—	—	—	—	900	—	T900D1-60M ^①		—	T900D2-60M ^①	
1062	1050	400	450	600	900	—	T900D1-48M ^①	—	10,830	T900D2-48M ^①	—	12,130
		—	—	—	—	1000	—	T1000D1-60M ^①		—	T1000D2-60M ^①	
1247	1215	400	500	800	1000	—	T1000D1-48M ^①	—	10,830	T1000D2-48M ^①	—	12,130
		—	—	—	—	1200	—	T1200D1-60M ^①		—	T1200D2-60M ^①	
1454	1370	500	600	900	1200	—	T1200D1-48M ^①	—	12,900	T1200D2-48M ^①	—	14,650
		—	—	—	—	1500	—	T1500D1-60M ^①		—	T1500D2-60M ^①	
1839	1823	600	700	1200	1500	—	T1500D1-48M ^①	—	21,000	T1500D2-48M ^①	—	22,750
		—	—	—	—	1800	—	T1800D1-60M ^①		—	T1800D2-60M ^①	

6

① Includes integrated shunt rated (AC1) bypass contactor as standard. For across the line rated (AC3) bypass contactors, see page 6.30.