



Type PST, Enclosed NEMA 1, Combination In-Line, 5 – 1000 HP

Connected In-Line

Max. motor current		Maximum horsepower					NEMA1, 480V Circuit breaker	NEMA1, 600V Circuit breaker	List Price	NEMA1, 480V Fused disconnect	NEMA 1, 600V Fused disconnect	List Price
UL	IEC	208V	240V	380V	480V	600V	Catalog Number	Catalog Number		Catalog Number	Catalog Number	
18	18	5	5	10	10	—	T010LB1-48E	—	\$ 2055	T010LF1-48A	—	\$ 2055
		—	—	—	—	15	—	T015LB1-60E		—	T015LF1-60A	
28	30	7.5	10	15	20	—	T020LB1-48J	—	2065	T020LF1-48B	—	2065
		—	—	—	—	25	—	T025LB1-60J		—	T025LF1-60B	
34	37	10	10	20	25	—	T025LB1-48K	—	2110	T025LF1-48B	—	2110
		—	—	—	—	30	—	T030LB1-60K		—	T030LF1-60B	
42	44	10	15	25	30	—	T030LB1-48L	—	2315	T030LF1-48C	—	2315
		—	—	—	—	40	—	T040LB1-60L		—	T040LF1-60C	
54	50	15	20	30	40	—	T040LB1-48N	—	2655	T040LF1-48C	—	2655
		—	—	—	—	50	—	T050LB1-60N		—	T050LF1-60C	
68	72	20	25	40	50	—	T050LB1-48R	—	2680	T050LF1-48C	—	2680
		—	—	—	—	60	—	T060LB1-60R		—	T060LF1-60C	
80	85	25	30	50	60	—	T060LB1-48S	—	3705	T060LF1-48D	—	3705
		—	—	—	—	75	—	T075LB1-60S		—	T075LF1-60D	
104	105	30	40	60	75	—	T075LB1-48T	—	3735	T075LF1-48D	—	3735
		—	—	—	—	100	—	T100LB1-60T		—	T100LF1-60D	
130	142	40	50	75	100	—	T100LB1-48V	—	5075	T100LF1-48D	—	5075
		—	—	—	—	125	—	T125LB1-60V		—	T125LF1-60D	
156	150	50	60	100	125	—	T125LB1-48X	—	5720	T125LF1-48E	—	5720
		—	—	—	—	150	—	T150LB1-60X		—	T150LF1-60E	
192	210	60	75	125	150	—	T150LB1-48Y	—	6170	T150LF1-48E	—	6170
		—	—	—	—	200	—	T200LB1-60Y		—	T200LF1-60E	
248	250	75	100	150	200	—	T200LB1-48Z	—	6650	T200LF1-48E	—	6650
		—	—	—	—	250	—	T250LB1-60Z		—	T250LF1-60E	
302	300	100	100	150	250	—	T250LB1-48B	—	7580	T250LF1-48F	—	7580
		—	—	—	—	300	—	T300LB1-60B		—	T300LF1-60F	
361	370	125	150	200	300	—	T300LB1-48CM [Ⓢ]	—	8860	T300LF1-48FM [Ⓢ]	—	8860
		—	—	—	—	350	—	T350LB1-60CM [Ⓢ]		—	T350LF1-60FM [Ⓢ]	
414	400	—	—	250	350	—	T350LB1-48DM [Ⓢ]	—	11,300	T350LF1-48FM [Ⓢ]	—	11,300
		—	—	—	—	400	—	T400LB1-60DM [Ⓢ]		—	T400LF1-60FM [Ⓢ]	
480	470	150	200	300	400	—	T400LB1-48EM [Ⓢ]	—	11,800	T400LF1-48GM [Ⓢ]	—	11,800
		—	—	—	—	500	—	T500LB1-60EM [Ⓢ]		—	T500LF1-60GM [Ⓢ]	
590	570	200	250	350	500	—	T500LB1-48GM [Ⓢ]	—	14,550	T500LF1-48HM [Ⓢ]	—	14,550
		—	—	—	—	600	—	T600LB1-60GM [Ⓢ]		—	T600LF1-60HB [Ⓢ]	
720	720	250	300	450	600	—	T600LB1-48JM [Ⓢ]	—	16,030	T600LF1-48HM [Ⓢ]	—	16,030
		—	—	—	—	700	—	T700LB1-60JM [Ⓢ]		—	T700LF1-60HB [Ⓢ]	
840	840	300	350	500	700	—	T700LB1-48JM [Ⓢ]	—	19,400	T700LF1-48JM [Ⓢ]	—	19,400
		—	—	—	—	800	—	T800LB1-60JM [Ⓢ]		—	T800LF1-60JB [Ⓢ]	
960	—	350	400	—	800	—	T800LB1-48KM [Ⓢ]	—	27,500	T800LF1-48JM [Ⓢ]	—	27,500
		—	—	—	—	900	—	T900LB1-60KM [Ⓢ]		—	T900LF1-60JB [Ⓢ]	
1062	1050	400	450	600	900	—	T900LB1-48KM [Ⓢ]	—	28,200	T900LF1-48KM [Ⓢ]	—	28,200
		—	—	—	—	1000	—	T1000LB1-60KM [Ⓢ]		—	T1000LF1-60KB [Ⓢ]	

Ⓢ Includes integrated shunt rated (AC1) bypass contactor as standard. For across the line rated (AC3) bypass contactors, see page 6.30.