

Type PST, Enclosed NEMA 1, Combination Inside Delta, 7.5 – 1900 HP



Connected Inside Delta

Max. motor current		Maximum horsepower					NEMA1, 480V Circuit breaker	NEMA1, 600V Circuit breaker	List Price	NEMA1, 480V Fused disconnect	NEMA 1, 600V Fused disconnect	List Price
UL	IEC	208V	240V	380V	480V	600V	Catalog Number	Catalog Number		Catalog Number	Catalog Number	
28	30	7.5	10	15	20	—	T020DB1-48J	—	\$ 2065	T020DF1-48B	—	\$ 2065
		—	—	—	—	25	—	T025DB1-60J		—	T025DF1-60B	
34	37	10	10	20	25	—	T025DB1-48K	—	2080	T025DF1-48B	—	2080
		—	—	—	—	30	—	T030DB1-60K		—	T030DF1-60B	
42	44	10	15	25	30	—	T030DB1-48L	—	2255	T030DF1-48C	—	2255
		—	—	—	—	40	—	T040DB1-60L		—	T040DF1-60C	
54	50	15	20	30	40	—	T040DB1-48N	—	2285	T040DF1-48C	—	2285
		—	—	—	—	50	—	T050DB1-60N		—	T050DF1-60C	
68	72	20	25	40	50	—	T050DB1-48R	—	2315	T050DF1-48C	—	2315
		—	—	—	—	60	—	T060DB1-60R		—	T060DF1-60C	
80	85	25	30	50	60	—	T060DB1-48S	—	3055	T060DF1-48D	—	3055
		—	—	—	—	75	—	T075DB1-60S		—	T075DF1-60D	
104	105	30	40	60	75	—	T075DB1-48T	—	3080	T075DF1-48D	—	3080
		—	—	—	—	100	—	T100DB1-60T		—	T100DF1-60D	
130	142	40	50	75	100	—	T100DB1-48V	—	3905	T100DF1-48D	—	3905
		—	—	—	—	125	—	T125DB1-60V		—	T125DF1-60D	
156	150	50	60	100	125	—	T125DB1-48X	—	4535	T125DF1-48E	—	4535
		—	—	—	—	150	—	T150DB1-60X		—	T150DF1-60E	
192	210	60	75	125	150	—	T150DB1-48Y	—	5675	T150DF1-48E	—	5675
		—	—	—	—	200	—	T200DB1-60Y		—	T200DF1-60E	
248	250	75	100	150	200	—	T200DB1-48Z	—	5720	T200DF1-48E	—	5720
		—	—	—	—	250	—	T250DB1-60Z		—	T250DF1-60E	
302	300	100	100	150	250	—	T250DB1-48B	—	6870	T250DF1-48F	—	6870
		—	—	—	—	300	—	T300DB1-60B		—	T300DF1-60F	
361	370	125	150	200	300	—	T300DB1-48C	—	7450	T300DF1-48F	—	7450
		—	—	—	—	350	—	T350DB1-60C		—	T350DF1-60F	
414	400	—	—	250	350	—	T350DB1-48D	—	8680	T350DF1-48F	—	8680
		—	—	—	—	400	—	T400DB1-60D		—	T400DF1-60F	
480	470	150	200	300	400	—	T400DB1-48E	—	9180	T400DF1-48G	—	9180
		—	—	—	—	500	—	T500DB1-60E		—	T500DF1-60G	
590	570	200	250	350	500	—	T500DB1-48GM [Ⓞ]	—	11,460	T500DF1-48HM [Ⓞ]	—	11,460
		—	—	—	—	600	—	T600DB1-60GM [Ⓞ]		—	T600DF1-60HM [Ⓞ]	
720	720	250	300	450	600	—	T600DB1-48JM [Ⓞ]	—	12,900	T600DF1-48HM [Ⓞ]	—	12,900
		—	—	—	—	700	—	T700DB1-60JM [Ⓞ]		—	T700DF1-60HM [Ⓞ]	
840	840	300	350	500	700	—	T700DB1-48JM [Ⓞ]	—	15,850	T700DF1-48JM [Ⓞ]	—	15,850
		—	—	—	—	800	—	T800DB1-60JM [Ⓞ]		—	T800DF1-60JM [Ⓞ]	
960	—	350	400	—	800	—	T800DB1-48KM [Ⓞ]	—	17,330	T800DF1-48JM [Ⓞ]	—	17,330
		—	—	—	—	900	—	T900DB1-60KM [Ⓞ]		—	T900DF1-60JM [Ⓞ]	
1062	1050	400	450	600	900	—	T900DB1-48KM [Ⓞ]	—	18,030	T900DF1-48KM [Ⓞ]	—	18,030
		—	—	—	—	1000	—	T1000DB1-60KM [Ⓞ]		—	T1000DF1-60KM [Ⓞ]	
1247	1215	400	500	800	1000	—	T1000DB1-48LM [Ⓞ]	—	20,830	T1000DF1-48KM [Ⓞ]	—	20,830
		—	—	—	—	1200	—	T1200DB1-60LM [Ⓞ]		—	T1200DF1-60KM [Ⓞ]	
1454	1370	500	600	900	1200	—	T1200DB1-48MM [Ⓞ]	—	22,900	T1200DF1-48LM [Ⓞ]	—	22,900
		—	—	—	—	1500	—	T1500DB1-60MM [Ⓞ]		—	T1500DF1-60LM [Ⓞ]	
1839	1823	600	700	1200	1500	—	T1500DB1-48NM [Ⓞ]	—	33,500	T1500DF1-48NM [Ⓞ]	—	33,500
		—	—	—	—	1800	—	T1800DB1-60NM [Ⓞ]		—	T1800DF1-60NM [Ⓞ]	

6

[Ⓞ] Includes integrated shunt rated (AC1) bypass contactor as standard. For across the line rated (AC3) bypass contactors, see page 6.30.