

Non-illuminated Potentiometers & reset actuator

Pilot Devices
Type CBG 30mm



CBG-KSP5K



CBG-KSP5K4XP



KPR3-104B3

Potentiometer — with terminal block & leads, UL Type 1

Resistance	Black plastic ring		Chrome metal ring	
	Catalog number	List price	Catalog number	List price
0 – 5 kilohm	CBG-KSP5K	\$ 125	CBG-MSP5K	\$ 125
0 – 10 kilohm	CBG-KSP10K		CBG-MSP10K	

Note: Both trimmers have resistive elements made from cermet. These types of trimmers are excellent for commercial applications. The cermet element provides a continuous contact surface for the wiper. A continuous contact surface allows the resistance value to be set closer to the desired value than a typical wire-wound resistor.

Potentiometer with 5 kΩ resistor — without terminal block & leads, UL type 1, 3R, 4, 4X, 12, 13

Bezel	Weight (Kg.)	Catalog number	List price
Black plastic	0.034	CBG-KSP5K4XP	\$ 105
Metal	0.042	CBG-MSP5K4XP	110

Potentiometer with 10 kΩ resistor

Bezel	Weight (Kg.)	Catalog number	List price
Black plastic	0.034	CBG-KSP10K4XP	\$ 105
Metal	0.042	CBG-MSP10K4XP	110

Operating knob

Bezel	Weight (Kg.)	Catalog number	List price
Black plastic	0.023	CBK-KKNOB	\$ 15
Metal	0.031	CBK-MKNOB	20

Nameplate

Bezel	Catalog number	List price
Nameplate	CBG-NPE/SP	\$ 10

Adaptor ring

Type	Catalog number	List price
Black plastic	CBK-PK3A	\$ 8
Chrome metal	CBK-PM3A	10

Technical data ①

Resistance range	0 to 5 kilohm for 5 kilohm potentiometer 0 to 10 kilohm for 10 kilohm potentiometer
Resistance tolerance	+/- 10%
Power rating	2W

Reset actuator, UL Type 4X

Item	Black plastic ring		Chrome metal ring	
	Catalog number	List price	Catalog number	List price
Black button with "RESET" engraved legend.	CBG-RB	\$ 18	CBG-MRB	\$ 18

① At room ambient: +25°C nominal and 50% relative humidity nominal.