

# Components

## 30mm, IP 65, UL Type 4

Plastic  
Limit switches

⊕ "N.C." contact with positive opening operation or element (subassembly, head, lever) suitable for positive opening operation.

**Warning! The positive opening operation of limit switch is only guaranteed if the elements noted with ⊕ are fitted.**



LS35P50B11



LSA30X41



LSA30X42



LSA30X51



LSA30X71



LSA30P05



LSA30P06



LSC30XD11



LSR1305

### Casings with angular motion head for adjustable rod or roller levers, delivered without actuator

Contact blocks						Positive opening operation	Actuation speed max. m/s	Unit weight kg (1 pc)	Catalog number	List price
B11	D11	C11	L02	L20	B02					
1						⊗	1.5	0.092	LS35P50B11	\$ 23
	1					⊗	1.5	0.092	LS35P50D11	24
		1				⊗	1.5	0.092	LS35P50C11	25
			1			⊗	1.5	0.092	LS35P50L02	25
				1		⊗	1.5	0.092	LS35P50L20	25
					1	⊗	1.5	0.092	LS35P50B02	25

### Actuators for LS35P40 (delivered with M3.5 screw)

#### To be actuated by 30° cam

- ⊕ ∅ 18mm polyamide roller lever ①
- ⊗ ∅ 45mm rubber roller lever ①

### Actuators for LS35P50 (delivered with M3.5 screw and adaptation parts)

#### To be actuated by 30° cam

- ⊗ ∅ 18mm adjustable polyamide roller lever ①
- ⊗ ∅ 45mm adjustable rubber roller lever ①

#### To be actuated by fully directional translation movement

- ⊗ ∅ 3mm adjustable inox rod lever, 170mm ①
- ⊗ ∅ 3mm adjustable fiberglass rod lever, 170mm ①
- ⊗ ∅ 6mm adjustable polyamide rod lever, 195mm ①
- ⊗ ∅ 6mm adjustable fiberglass rod lever, 195mm ①

### Right angle key for LS35P15

- ⊕ Right angle key (mounting 13mm)

### Straight key for LS35P16

- ⊕ Straight key (mounting 13mm)

### Separate contact blocks

- ⊕ 1 NC & 1 NO 2-pole snap action
- ⊕ 1 NC & 1 NO 2-pole non-overlapping slow action
- ⊕ 1 NO & 1 NC 2-pole non-overlapping slow action
- ⊕ 2 NC 2-pole simultaneous slow action
- ⊗ 2 NO 2-pole simultaneous slow action
- ⊕ 2 NC 2-pole snap action

### 1/2" NPT plastic adaptors

- 1 piece

① Free position adjustment of lever 10° by 10° over 360°.

9